



US010024069B2

(12) **United States Patent**  
**Bond et al.**

(10) **Patent No.:** **US 10,024,069 B2**  
(45) **Date of Patent:** **Jul. 17, 2018**

(54) **CONSTRUCTION PROP ASSEMBLY**

E04G 11/486; E04G 25/065; E04G 25/04;  
E04G 25/06; E04G 2025/042; F16M  
13/027; F16M 13/022  
USPC ..... 248/235, 295.11, 297.51, 297.31, 243,  
248/200.1, 351, 354.1, 354.3, 354.6, 357;  
249/18

(71) Applicant: **Concrete Support Systems of  
Houston, LLC**, Houston, TX (US)

See application file for complete search history.

(72) Inventors: **Bradley D. A. Bond**, Katy, TX (US);  
**Gunter Sengel**, Naples, FL (US); **Mark  
Grace**, Rochester, NY (US)

(56) **References Cited**

(73) Assignee: **Concrete Support Systems**, Houston,  
TX (US)

U.S. PATENT DOCUMENTS

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 746 days.

337,601 A 3/1886 Merrill  
1,382,505 A \* 6/1921 Hargey ..... B25B 1/2484  
211/86.01

(Continued)

(21) Appl. No.: **14/542,331**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Nov. 14, 2014**

WO WO2009009898 A1 1/2009

(65) **Prior Publication Data**

US 2016/0060882 A1 Mar. 3, 2016

*Primary Examiner* — Anita M King

(74) *Attorney, Agent, or Firm* — Shannon L Warren

**Related U.S. Application Data**

(60) Provisional application No. 62/044,662, filed on Sep.  
2, 2014.

(57) **ABSTRACT**

(51) **Int. Cl.**

**E04G 11/00** (2006.01)  
**E04G 11/38** (2006.01)  
**E04G 11/48** (2006.01)  
**E04G 25/06** (2006.01)  
**E04G 25/04** (2006.01)

A construction beam head assembly comprising an improved forming system having one or more fixed beam-head prop assemblies each having an upper portion and a lower portion. The upper portion having a screw-jack threaded shaft assembly and a drop-head The lower portion comprising of a prop and a collar The screw-jack threaded shaft assembly having an external diameter and an external threading The screw-jack threaded shaft assembly attaches to the drop-head The upper portion selectively slides into the lower portion The collar having an internal threading and an internal diameter The internal threading of the collar rotatably attaches to the external threading of the screw-jack threaded shaft assembly of the upper portion. The upper portion and the lower portion adjustably attach to one another with the collar and the screw-jack threaded shaft assembly to provide a variable height of the prop assembly.



(52) **U.S. Cl.**

CPC ..... **E04G 11/38** (2013.01); **E04G 11/48**  
(2013.01); **E04G 11/483** (2013.01); **E04G**  
**11/486** (2013.01); **E04G 25/065** (2013.01);  
**E04G 2025/042** (2013.01)

(58) **Field of Classification Search**

CPC ..... E04G 11/38; E04G 11/48; E04G 11/483;

**16 Claims, 13 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

1,781,063 A \* 11/1930 Jessen ..... E04G 25/06  
248/354.4  
3,822,850 A \* 7/1974 Elias ..... E04G 21/3233  
248/200.1  
4,122,645 A \* 10/1978 Tooley ..... E04G 11/486  
248/354.3  
5,031,724 A \* 7/1991 Quinn ..... E04G 25/06  
182/186.6  
5,590,863 A \* 1/1997 Sasaki ..... E04G 17/14  
248/354.3  
5,758,854 A \* 6/1998 Shih ..... F16B 37/0864  
248/354.3  
6,481,912 B2 \* 11/2002 Shih ..... E04G 7/12  
24/483  
6,612,533 B2 \* 9/2003 Biles ..... B25H 3/006  
248/125.1  
7,584,932 B2 9/2009 Shih  
8,066,247 B2 \* 11/2011 Spera ..... E04G 11/38  
248/354.1  
8,616,519 B2 \* 12/2013 Bacon ..... E04G 11/483  
249/18  
2007/0264076 A1 11/2007 McCracken

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3A






FIG. 3B






FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 7A






FIG. 7B






FIG. 9A

FIG. 9B




FIG. 10A




FIG. 10B




FIG. 11A




FIG. 11B




FIG. 12

PRIOR ART




FIG. 13A




FIG. 13B

1

**CONSTRUCTION PROP ASSEMBLY****CROSS-REFERENCE TO RELATED APPLICATIONS**

This application claims benefit to provisional U.S. Patent Application No. 62/044,662, filed on 2014 Sep. 2.

**STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT (IF APPLICABLE)**

Not applicable.

**REFERENCE TO SEQUENCE LISTING, A TABLE, OR A COMPUTER PROGRAM LISTING COMPACT DISC APPENDIX (IF APPLICABLE)**

Not applicable.

**BACKGROUND OF THE INVENTION**

This disclosure relates generally to an improved construction beam head assembly. Examples of construction props can be found in the following list of prior art references: U.S. Pat. No. 3,376,011 A, US 20070264076 A1, WO 2009009898 A1, and U.S. Pat. No. 7,584,932 B2.

None of the above inventions and patents, taken either singularly or in combination, is seen to describe the instant disclosure as claimed. Accordingly, an improved construction beam head assembly would be advantageous.

**SUMMARY OF THE INVENTION**

Two system and a method of use are disclosed.

First, an improved grid shoring system comprising a one or more fixed beam-head prop assemblies supporting a one or more beams is disclosed. Each of said one or more fixed beam-head prop assemblies comprise an upper portion, a lower portion, a variable height, and a threaded collar. Said upper portion having a screw-jack threaded shaft assembly. Said screw-jack threaded shaft assembly comprises a threaded shaft having an external diameter and an external threading and an upper attachment plate having a plurality of fastening apertures. Said upper portion of said one or more fixed beam-head prop assemblies selectively slide into said lower portion of said one or more fixed beam-head prop assemblies. Said threaded collar comprises an internal threading and an internal diameter. Said internal threading of said threaded collar rotateably attaches to said external threading of said screw-jack threaded shaft assembly of said upper portion. Said lower portion comprises a lower central shaft having an internal diameter being larger than said external diameter of said threaded shaft. Said upper portion and said lower portion adjustably attach to one another by selectively sliding said threaded shaft in an up and down direction through said lower central shaft of said lower portion. Vertically adjusting said threaded collar along said threaded shaft to select said variable height. Said upper portion comprises a first end cap seat. Said lower portion comprises a second end cap seat. Said upper portion having a drop-head. Said drop-head comprises a bottom plate having a plurality of fastening apertures. Said screw-jack threaded shaft assembly attaches to said drop-head by aligning said plurality of fastening apertures of said bottom plate of said drop-head with said plurality of fastening apertures of said upper attachment plate of said screw-jack threaded

2

shaft assembly, and inserting and locking a one or more nut and bolt assemblies through said plurality of fastening apertures in said bottom plate and said upper attachment plate. Said first end cap seat is selectively attached to said drop-head of said upper portion. Said first end cap seat comprises a variable height. Adjusting said variable height of said first end cap seat comprises adjusting said threaded collar between said upper portion and said lower portions of said one or more fixed beam-head prop assemblies. Said lower portion comprising of a prop and a fixed beam-head. Said fixed beam-head comprising a central shaft having a central shaft having an internal diameter, a first end and a second end, a bottom plate having a plurality of fastening apertures, and a second end cap seat attached around and to said central shaft. Said prop comprising a central shaft having a first end and a second end, and a top plate having a plurality of fastening apertures. Said central shaft of said prop comprises central shaft having a first end aperture and an internal diameter; and Said plurality of fastening apertures of said top plate of said prop align and attach to said plurality of fastening apertures of said bottom plate of said fixed beam-head.

Next, an improved grid shoring system comprising a one or more fixed beam-head prop assemblies supporting a one or more beams. Each of said one or more fixed beam-head prop assemblies comprise an upper portion, a lower portion, a variable height, and a threaded collar. Said upper portion having a screw-jack threaded shaft assembly. Said screw-jack threaded shaft assembly comprises a threaded shaft having an external diameter and an external threading and an upper attachment plate having a plurality of fastening apertures. Said upper portion of said one or more fixed beam-head prop assemblies selectively slide into said lower portion of said one or more fixed beam-head prop assemblies. Said threaded collar comprises an internal threading and an internal diameter. Said internal threading of said threaded collar rotateably attaches to said external threading of said screw-jack threaded shaft assembly of said upper portion. Said lower portion comprises a lower central shaft having an internal diameter being larger than said external diameter of said threaded shaft. Said upper portion and said lower portion adjustably attach to one another by selectively sliding said threaded shaft in an up and down direction through said lower central shaft of said lower portion, and vertically adjusting said threaded collar along said threaded shaft to select said variable height. Said upper portion comprises a first end cap seat; and Said lower portion comprises a second end cap seat.

Finally, a method of using an improved grid shoring system is disclosed. Said method comprising: supporting a one or more beams on a first end cap seat and a second end cap seat of a one or more fixed beam-head prop assemblies; selectively adjusting a height of said first end cap seat by sliding a threaded shaft in an up and down direction through a lower central shaft of a lower portion, and vertically adjusting a threaded collar along said threaded shaft to select a variable height. Said one or more fixed beam-head prop assemblies comprise Said lower portion having a central shaft, an upper portion having said threaded shaft, Said threaded collar.

**BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING**

FIG. 1 illustrates an elevated front view an improved grid shoring system comprising of a one or more fixed beam-head prop assemblies and a one or more beams.

FIG. 2 illustrates a perspective overview of an improved grid shoring system.

FIGS. 3A and 3B illustrate a perspective overview of a drop-head and of a fixed beam-head.

FIGS. 4A and 4B illustrate a perspective overview of said prop assembly.

FIG. 4A comprises dashed lines to indicate which portions of said prop assembly are illustrated in FIG. 4B.

FIGS. 5A and 5B illustrate a solid line and a cross-section perspective overview of said threaded collar.

FIGS. 6A, 6B, 6C and 6D illustrate a solid view and a cross-section perspective overview of said drop-head and of said fixed beam-head.

FIGS. 7A and 7B illustrate a solid view and a cross-section perspective overview of said screw-jack threaded shaft assembly.

FIGS. 8A and 8B illustrate a solid view and a cross-section perspective overview perspective overview of said prop.

FIGS. 9A and 9B illustrate a cross-section perspective overview and a cross-section elevated front view of said prop assembly.

FIG. 9A comprises dashed lines to indicate which portions of said prop assembly are illustrated in FIG. 9B.

FIGS. 10A and 10B illustrate two elevated front views of said prop assembly, first in a tall configuration having a first height and a then in a short configuration having a second height.

FIGS. 11A and 11B illustrate two perspective cross-section overviews of said prop assembly, first in said tall configuration and then in said short configuration.

FIG. 12 illustrates said prop assembly in an exploded perspective overview.

FIGS. 13A and 13B illustrate a perspective overview and an elevated front view of a prior art grid system.

#### DETAILED DESCRIPTION OF THE INVENTION

Described herein is an improved construction beam head assembly. The following description is presented to enable any person skilled in the art to make and use the invention as claimed and is provided in the context of the particular examples discussed below, variations of which will be readily apparent to those skilled in the art. In the interest of clarity, not all features of an actual implementation are described in this specification. It will be appreciated that in the development of any such actual implementation (as in any development project), design decisions must be made to achieve the designers' specific goals (e.g., compliance with system- and business-related constraints), and that these goals will vary from one implementation to another. It will also be appreciated that such development effort might be complex and time-consuming, but would nevertheless be a routine undertaking for those of ordinary skill in the field of the appropriate art having the benefit of this disclosure. Accordingly, the claims appended hereto are not intended to be limited by the disclosed embodiments, but are to be accorded their widest scope consistent with the principles and features disclosed herein.

FIG. 1 illustrates an elevated front view an improved grid shoring system 102 comprising of a one or more fixed beam-head prop assemblies and a one or more beams. In one embodiment, said one or more fixed beam-head prop assemblies can comprise a first assembly 100a, a second assembly 100b and a third assembly 100c. Hereafter, all of said one or more fixed beam-head prop assemblies can be referred to

collectively as a prop assembly 100 (which for this disclosure will be described in more detail as follows). In one embodiment, said one or more beams can comprise a first beam 104a, a second beam 104b, and a third beam 104c, as is known in the art. In one embodiment, said improved construction beam head assembly can comprise an improved method of setting said one or more fixed beam-head prop assemblies to various heights as disclosed herein.

This illustration includes a traditional prop assembly 120, which can comprise a prior art version of said prop assembly 100. Said improved grid shoring system 102 includes said traditional prop assembly 120 as an illustrative element, but said traditional prop assembly 120 is not required to make one of said improved grid shoring system 102. However, said improved grid shoring system 102 can comprise a one or more of a prior art elements, such as said traditional prop assembly 120.

FIG. 2 illustrates a perspective overview of said improved grid shoring system 102. In one embodiment, said improved grid shoring system 102 can comprise an example of a grid and panelized system, as is known in the art. In one embodiment, said improved grid shoring system 102 can comprise said one or more fixed beam-head prop assemblies, configured in a grid (such as an array pattern) and releasably attached to one another by a one or more beams (which can comprise of a plurality of a main beam 204 and/or a secondary beam 206). In one embodiment, said main beam 204 can be referred to as a "stringer" and said secondary beam 206 can be referred to as a "joist", as is known in the art. Further, atop of said beams, a one or more of a panel 202 and/or a plywood sheet 208 can be used to create a concrete working surface, as is known in the art.

In one embodiment, forming said improved grid shoring system 102 can comprise: adjusting a height of each among a one or more fixed beam-head prop assemblies 100; arranging said one or more fixed beam-head prop assemblies 100; attaching said one or more fixed beam-head prop assemblies 100 to one another with a one or more beams; and attaching a one or more panels to said one or more beams.

In one embodiment, said improved grid shoring system 102 can comprise said traditional prop assembly 120, lacking features disclosed herein. In one embodiment, said traditional prop assembly 120 lacks the ability to create a variable height for said one or more fixed beam-head prop assemblies, such as said first assembly 100a. That is, in one embodiment, said prop assembly 100 comprises two different variable shoring heights, whereas said traditional prop assembly 120 only has one.

FIGS. 3A and 3B illustrate a perspective overview of a drop-head 300 and of a fixed beam-head 301. In one embodiment, said one or more beams can selectively attach to said drop-head 300. In one embodiment, removing said one or more beams from said drop-head 300 can comprise striking a strike point 302 with a tool (such as a hammer). In one embodiment, said one or more beams will release from said 300 after such a strike, as is known in the art. In one embodiment, referring to said improved grid shoring system 102 as a "grid" can mean that said secondary beam 206 and said main beam 204 are installed onto said fixed beam-head 301 and/or said drop-head 300 at the same height as one another, rather than stacked on one another, as would be common in a "loose" system. In one embodiment, said one or more beams can each comprise an end cap 310 at their ends, as is known in the art. In one embodiment, said end cap 310 can selectively attach to said fixed beam-head 301 and/or said drop-head 300. In one embodiment, said fixed beam-head 301 can be attached to a portion of said first

assembly **100a** with a bolt assembly **312b**, and said drop-head **300** can be attached to a portion of said first assembly **100a** with a bolt assembly **312a**.

FIGS. 4A and 4B illustrate a perspective overview of said prop assembly **100**. FIG. 4A comprises dashed lines to indicate which portions of said prop assembly **100** are illustrated in FIG. 4B. In one embodiment, said prop assembly **100** can comprise an upper portion **400a** and a lower portion **400b**. In one embodiment, said upper portion **400a** can comprise said drop-head **300** and a screw-jack threaded shaft assembly **404**. In one embodiment, said lower portion **400b** can comprise a prop **402** and said fixed beam-head **301**. In one embodiment, said prop assembly **100** further comprises a threaded collar **406**.

In one embodiment, said upper portion **400a** and said lower portion **400b** move relative to one another so as to adjustably change a height **410** of said prop assembly **100**. In one embodiment, adjusting said height **410** can comprise rotating said threaded collar **406** relative to said screw-jack threaded shaft assembly **404**, as discussed below.

In one embodiment, said prop assembly **100** can comprise a first end cap seat **430a** attached to a portion of said upper portion **400a** and a second end cap seat **430b** attached to a portion of said lower portion **400b**.

In one embodiment, said lower portion **400b** can comprise a prop lock **412**, a lower exterior portion **414**, and an upper interior portion **416**. In one embodiment, said lower exterior portion **414** can receive a portion of said upper interior portion **416** allowing said upper interior portion **416** to slide in and out of said lower exterior portion **414** freely. In one embodiment, said prop lock **412** can hold said upper interior portion **416** to said lower exterior portion **414**, as is known in the art. Accordingly, said second end cap seat **430b** of said lower portion **400b** can comprise a variable height **440b** as set by adjusting said lower exterior portion **414** and said upper interior portion **416** of said prop **402** with said prop lock **412**.

Likewise, said first end cap seat **430a** can comprise a variable height **440a** as set by said prop **402** and/or said screw-jack threaded shaft assembly **404**, each of which are adjustable in their heights, as disclosed and illustrated herein. In one embodiment, adjusting said variable height **440a** can comprise adjusting said upper portion **400a** relative to said lower portion **400b** as discussed to follow.

FIGS. 5A and 5B illustrate a solid line and a cross-section perspective overview of said threaded collar **406**. In one embodiment, said threaded collar **406** can comprise a central collar aperture **502** having an internal diameter **504**, and an external diameter **505**. In one embodiment, said central collar aperture **502** can comprise a substantially cylindrical shape and an internal threading **506**. In one embodiment, said central collar aperture **502** can comprise an inner surface of a ring portion **508** of said threaded collar **406**. In one embodiment, said threaded collar **406** can further comprise a first handle **510a** and a second handle **510b**, capable of providing a leverage point to apply torque to said threaded collar **406**, as necessary.

FIGS. 6A, 6B, 6C and 6D illustrate a solid view and a cross-section perspective overview of said drop-head **300** and of said fixed beam-head **301**. In one embodiment, said drop-head **300** can comprise a central shaft **602**, a drop-head top plate **604**, a bottom plate **606**, a first end cap seat **430a**, a star **610** and a central drop-head aperture **612**, as is known in the art. In one embodiment, said bottom plate **606** can comprise a plurality of fastening apertures which can comprise a first aperture **620a** and a second aperture **620b**.

In one embodiment, said fixed beam-head **301** can comprise a second end cap seat **430b**, a central shaft **602b**, a fixed beam-head top plate **604b**, a central fixed beam-head aperture **612b** and a bottom plate **606b**. In one embodiment, said second end cap seat **430b** can be attached to said central shaft **602b** of said fixed beam-head **301** at a welding point **622**. In one embodiment, said fixed beam-head **301** can comprise said second end cap seat **430b** in a fixed location which cannot be easily be removed in the manner that said first end cap seat **430a** is removed from said drop-head **300**. In one embodiment, said bottom plate **606b** can comprise a plurality of fastening apertures which can comprise a first aperture **630a** and a second aperture **630b**. As illustrated in FIG. 6D, said fixed beam-head **301** can comprise a single weld-free uniform body, or can comprise two or more pieces having been welded together, as described above. In one embodiment, said central fixed beam-head aperture **612b** of said fixed beam-head **301** can comprise an internal diameter **650**. In one embodiment, said central shaft **602b** can comprise a first end **652a** and a second end **652b**. In one embodiment, said fixed beam-head top plate **604b** is attached or uniformly a portion of said central shaft **602b** at said first end **652a**; and said bottom plate **606b** is attached or uniformly a portion of said central shaft **602b** at said second end **652b**. In one embodiment, said fixed beam-head top plate **604b** can comprise a platform **654** whereupon said threaded collar **406** can sit when said upper portion **400a** is inserted into a portion of said lower portion **400b**. In one embodiment, said central shaft **602b** can comprise a first end opening **656a** at said first end **652a** and a second end opening **656b** at said second end **652b**.

In one embodiment, said drop-head **300** can comprise an external pin **615** and a one or more stop-tabs **640**, as is known in the art. In one embodiment, said first end cap seat **430a** and said star **610** can be held between said external pin **615** and said one or more stop-tabs **640**. In one embodiment, said fixed beam-head **301** can comprise said one or more stop-tab **640**, but not always, as illustrated here.

FIGS. 7A and 7B illustrate a solid view and a cross-section perspective overview of said screw-jack threaded shaft assembly **404**. In one embodiment, said screw-jack threaded shaft assembly **404** can comprise a threaded shaft **702** and an upper attachment plate **704**. In one embodiment, said threaded shaft **702** can comprise an external threading **706**; and said upper attachment plate **704** can comprise a plurality of fastening apertures (which can comprise a first aperture **708a** and a second aperture **708b**). In one embodiment, said threaded shaft **702** can comprise a substantially cylindrical shape being of an external diameter **710** appropriate for threading through said central collar aperture **502**, as is known in the art. Thus, in one embodiment said external diameter **710** of said threaded shaft **702** is equal to or smaller than said internal diameter **504** of said central collar aperture **502** of said threaded collar **406**. In one embodiment, said threaded shaft **702** can comprise a central screw-jack aperture **720** which can comprise a substantially cylindrical tube shape having an opening at it endings.

FIGS. 8A and 8B illustrate a solid view and a cross-section perspective overview perspective overview of said prop **402**. In one embodiment, said prop **402** can comprise a central shaft **802** (having a first end **803a** and a second end **803b**), a first end aperture **804** (at said first end **803a**), a prop top plate **806**, and a foot **808**, and a central prop aperture **820** (which can comprise a substantially cylindrical tube shape having an opening at it endings) as is known in the art. In one embodiment, said central prop aperture **820** can comprise an internal diameter **828** at said first end **803a**. In one

embodiment, said prop top plate **806** can comprise a plurality of fastening apertures (which can comprise a first aperture **822a**, a second aperture **822b**, a third aperture **822c**, and a fourth aperture **822d**).

In one embodiment, said upper interior portion **416** of said prop **402** can comprise a plurality of side apertures (which can comprise a first aperture **830a**, a second aperture **830b**, a third aperture **830c**, a fourth aperture **830d**, a fifth aperture **830e**, a sixth aperture **830f**, a seventh aperture **830g**, and an eighth aperture **830h**). In one embodiment, attaching said upper interior portion **416** to said lower exterior portion **414** can comprise: aligning said plurality of side apertures of said upper interior portion **416** with an exterior aperture **840** of said lower exterior portion **414**; inserting a locking element **842** through said exterior aperture **840** and one of said plurality of side apertures; and locking said prop lock **412** in place, as is known in the art. In one embodiment, said prop lock **412** can comprise a threaded ring **852** which selectively attaches to an external threading **850** of said lower exterior portion **414**.

FIGS. **9A** and **9B** illustrate a cross-section perspective overview and a cross-section elevated front view of said prop assembly **100**. FIG. **9A** comprises dashed lines to indicate which portions of said prop assembly **100** are illustrated in FIG. **9B**. In one embodiment, a portion of said threaded shaft **702** selectively slides into and out of a lower central shaft **920** (which can comprise said central fixed beam-head aperture **612b** and said central prop aperture **820**). In one embodiment, said threaded collar **406** provides a relative locking mechanism for holding said upper portion **400a** (that is said screw-jack threaded shaft assembly **404** and said drop-head **300**) to a particular height above said lower portion **400b**.

In one embodiment, said bottom plate **606** of said drop-head **300** releaseably attaches to said upper attachment plate **704** with a one or more nut and bolt assemblies **904**, as is known in the art. Likewise, in one embodiment, said prop top plate **806** releaseably attaches to said bottom plate **606b** with a one or more nut and bolt assemblies **904**, as is known in the art.

In one embodiment, said lower central shaft **920** of said lower portion **400b** comprises said internal diameter **830** being larger than said external diameter **710** of said threaded shaft **702**. In one embodiment, said upper portion **400a** adjustably attaches to said lower portion **400b** by: selectively sliding said threaded shaft **702** in an up and down direction through said lower central shaft **920** of said lower portion **400b**; and vertically adjusting said threaded collar **406** along said threaded shaft **702** to fix a variable height of said prop assembly **100**.

FIGS. **10A** and **10B** illustrate two elevated front views of said prop assembly **100**, first in a tall configuration **1000a** having a first height **1002a** and a then in a short configuration **1000b** having a second height **1002b**.

FIGS. **11A** and **11B** illustrate two perspective cross-section overviews of said prop assembly **100**, first in said tall configuration **1000a** and then in said short configuration **1000b**. In one embodiment, said screw-jack threaded shaft assembly **404** can retract into said lower portion **400b** (that is said prop **402** and said threaded collar **406**) to a small overlap **1102a** or a large overlap **1102b**, as illustrated. In one embodiment, said small overlap **1102a** can comprise a less stable version of said prop assembly **100** since lateral pressures put on said prop assembly **100** may cause said threaded collar **406** and/or said screw-jack threaded shaft

assembly **404** to become disengaged from said lower portion **400b**, accordingly, said large overlap **1102b** can be safer than said small overlap **1102a**.

FIG. **12** illustrates said prop assembly **100** in an exploded perspective overview.

FIGS. **13A** and **13B** illustrate a perspective overview and an elevated front view of a prior art grid system **1302**. In one embodiment, said prior art grid system **1302** can comprise a plurality of traditional props (which can comprise a first traditional prop **1304a**, a second traditional prop **1304b**, a third traditional prop **1304c**, a fourth traditional prop **1304d**, a fifth traditional prop **1304e**, a sixth traditional prop **1304f**, a seventh traditional prop **1304g**, an eighth traditional prop **1304h**, a ninth traditional prop **1304k**, a tenth traditional prop **1304m**, a eleventh traditional prop **1304n**, and a twelfth traditional prop **1304p**). In one embodiment, said plurality of traditional props can comprise embodiments of said traditional prop assembly **120**, and therefore, said prior art grid system **1302** can comprise a prior art illustration.

In one embodiment, said prior art grid system **1302** can comprise of a one or more sets of props and beams (which can comprise a first set **1308a** having a first height **1306a**, a second set **1308b** having a second height **1306b**, and a third set **1308c** having a third height **1306c**). In one embodiment, said one or more sets of props and beams can be arranged with an overlap between each set so as to accommodate different height preferences for said beams. For example, in one embodiment, said first set **1308a** can be at said first height **1306a** and said second set **1308b** can be at said second height **1306b**, and an overlapping portion **1310a** can be included. Likewise, an overlapping portion **1310b** can be used between said second set **1308b** and said third set **1308c**, as illustrated.

Various changes in the details of the illustrated operational methods are possible without departing from the scope of the following claims. Some embodiments may combine the activities described herein as being separate steps. Similarly, one or more of the described steps may be omitted, depending upon the specific operational environment the method is being implemented in. It is to be understood that the above description is intended to be illustrative, and not restrictive. For example, the above-described embodiments may be used in combination with each other. Many other embodiments will be apparent to those of skill in the art upon reviewing the above description. The scope of the invention should, therefore, be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled. In the appended claims, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein.”

The invention claimed is:

1. An improved grid shoring system comprising:
  - one or more fixed beam-head prop assemblies supporting one or more beams;
  - each of said one or more fixed beam-head prop assemblies comprise an upper portion, a lower portion, a variable height, and a threaded collar;
  - said upper portion having a screw-jack threaded shaft assembly;
  - said screw-jack threaded shaft assembly comprises
    - a threaded shaft having an external diameter and an external threading and
    - an upper attachment plate having a plurality of fastening apertures;

said upper portion of said one or more fixed beam-head prop assemblies selectively slide into said lower portion of said one or more fixed beam-head prop assemblies;

said threaded collar comprises an internal threading and an internal diameter;

said internal threading of said threaded collar rotateably attaches to said external threading of said screw-jack threaded shaft assembly of said upper portion;

said lower portion comprises a lower central shaft having an internal diameter being larger than said external diameter of said threaded shaft;

said upper portion and said lower portion adjustably attach to one another by selectively sliding said threaded shaft in an up and down direction through said lower central shaft of said lower portion, and vertically adjusting said threaded collar along said threaded shaft to select said variable height;

said upper portion comprises a first end cap seat;

said lower portion comprises a second end cap seat;

said upper portion having a drop-head;

said drop-head comprises a bottom plate having a plurality of fastening apertures;

said screw-jack threaded shaft assembly attaches to said drop-head by aligning said plurality of fastening apertures of said bottom plate of said drop-head with said plurality of fastening apertures of said upper attachment plate of said screw-jack threaded shaft assembly, and inserting and locking one or more nut and bolt assemblies through said plurality of fastening apertures in said bottom plate and said upper attachment plate;

said first end cap seat is selectively attached to said drop-head of said upper portion;

said first end cap seat comprises a variable height;

adjusting said variable height of said first end cap seat comprises adjusting said threaded collar between said upper portion and said lower portion of said one or more fixed beam-head prop assemblies;

said lower portion comprising of a prop and a fixed beam-head;

said fixed beam-head comprising

- a central shaft having a central fixed beam-head aperture having an internal diameter, a first end and a second end,
- a bottom plate having a plurality of fastening apertures, and
- a second end cap seat attached around and to said central shaft;

said prop comprising

- a central shaft having a first end and a second end, and
- a prop top plate having a plurality of fastening apertures;

said central shaft of said prop comprises central prop aperture having a first end aperture and an internal diameter; and

said plurality of fastening apertures of said prop top plate of said prop align and attach to said plurality of fastening apertures of said bottom plate of said fixed beam-head.

**2.** An improved grid shoring system comprising: one or more fixed beam-head prop assemblies supporting one or more beams;

each of said one or more fixed beam-head prop assemblies comprise an upper portion, a lower portion, a variable height, and a threaded collar;

said upper portion having a screw-jack threaded shaft assembly;

said screw-jack threaded shaft assembly comprises a threaded shaft having an external diameter and an external threading and an upper attachment plate having a plurality of fastening apertures;

said upper portion of said one or more fixed beam-head prop assemblies selectively slide into said lower portion of said one or more fixed beam-head prop assemblies;

said threaded collar comprises an internal threading and an internal diameter;

said internal threading of said threaded collar rotateably attaches to said external threading of said screw-jack threaded shaft assembly of said upper portion;

said lower portion comprises a lower central shaft having an internal diameter being larger than said external diameter of said threaded shaft;

said upper portion and said lower portion adjustably attach to one another by selectively sliding said threaded shaft in an up and down direction through said lower central shaft of said lower portion, and vertically adjusting said threaded collar along said threaded shaft to select said variable height;

said upper portion comprises a first end cap seat;

said lower portion comprises a second end cap seat;

said upper portion comprises a drop-head;

said drop-head comprises a bottom plate having a plurality of fastening apertures;

said screw-jack threaded shaft assembly attaches to said drop-head by aligning said plurality of fastening apertures of said bottom plate of said drop-head with said plurality of fastening apertures of said upper attachment plate of said screw-jack threaded shaft assembly, and inserting and locking one or more nut and bolt assemblies through said plurality of fastening apertures in said bottom plate and said upper attachment plate;

said drop-head comprising a first end cap seat, a star and an external pin.

**3.** The improved grid shoring system of claim 2, wherein: said plurality of apertures of said upper attachment plate comprises at least a first aperture and a second aperture; said plurality of apertures of said bottom plate of said drop-head comprises at least a first aperture and a second aperture; and at least said first aperture and said second aperture of said bottom plate of said drop-head and said upper attachment plate of said screw-jack threaded shaft assembly align with one another and receive said one or more nut and bolt assemblies to hold said drop-head to said screw-jack threaded shaft assembly.

**4.** The improved grid shoring system of claim 2, wherein: said first end cap seat is selectively attached to said drop-head of said upper portion; said first end cap seat comprises a variable height; and adjusting said variable height of said first end cap seat comprises adjusting said threaded collar between said upper portion and said lower portion of said one or more fixed beam-head prop assemblies.

**5.** The improved grid shoring system of claim 2, further comprising: said threaded collar comprises a ring portion having a central collar aperture;

## 11

said central collar aperture being cylindrical and having said internal threading and said internal diameter; and said threaded collar further comprising a first handle extending out from said ring portion and providing leverage for turning said threaded collar relative to said screw-jack threaded shaft assembly.

6. The improved grid shoring system of claim 2, further comprising forming said improved grid shoring system with said one or more fixed beam-head prop assemblies by: adjusting a height of each among said one or more fixed beam-head prop assemblies, arranging said one or more fixed beam-head prop assemblies, attaching said one or more fixed beam-head prop assemblies to one another with said one or more beams, and attaching one or more panels to said one or more beams.

7. The improved grid shoring system of claim 2, wherein: said lower portion comprising of a prop and a fixed beam-head; said fixed beam-head comprising a central shaft having a central fixed beam-head aperture having an internal diameter, a first end and a second end, a bottom plate having a plurality of fastening apertures, and a second end cap seat attached around and to said central shaft of said fixed beam-head; said prop comprising a central shaft having a first end and a second end, and a prop top plate having a plurality of fastening apertures; said central shaft of said prop comprises central prop aperture having a first end aperture and an internal diameter; and said plurality of fastening apertures of said prop top plate of said prop align and attach to said plurality of fastening apertures of said bottom plate of said fixed beam-head.

8. The improved grid shoring system of claim 7, wherein: said prop comprises a prop lock, an upper interior portion and a lower exterior portion; said prop lock selectively attaches to a portion of said lower exterior portion of said prop; said upper interior portion comprises a plurality of side apertures; and said lower exterior portion attaches to said upper interior portion by aligning an external aperture of said lower exterior portion with a one of said plurality of side apertures, inserting a locking element through said external aperture and said one of said plurality of side apertures, and locking said prop lock in place.

9. The improved grid shoring system of claim 7, wherein: said prop comprises a foot at said second end of said central shaft of said prop.

10. The improved grid shoring system of claim 7, wherein: said second end cap seat of said fixed beam-head is welded to said central shaft of said fixed beam-head at a welding point.

11. The improved grid shoring system of claim 7, wherein:

## 12

said fixed beam-head comprises a fixed beam-head top plate comprising a platform; said threaded collar sits on said platform when a portion of said upper portion is inserted into a portion of said lower portion; said threaded collar comprises a ring portion having a central shaft; said ring portion having an internal diameter; and said external diameter of said ring portion of said threaded collar is larger than said internal diameter of said central shaft of said fixed beam-head.

12. The improved grid shoring system of claim 7, further comprising: an upper portion having a drop-head; a first end cap seat being selectively attached to said drop-head; and said second end cap seat of said fixed beam-head is affixed to said fixed beam-head.

13. A method of using an improved grid shoring system, comprising: supporting one or more beams on a first end cap seat and a second end cap seat of one or more fixed beam-head prop assemblies; selectively adjusting a height of said first end cap seat by sliding a threaded shaft in an up and down direction through a lower central shaft of a lower portion, and vertically adjusting a threaded collar along said threaded shaft to select a variable height; attaching a lower exterior portion of a prop to an upper interior portion comprises aligning an external aperture of said lower exterior portion with a one of said plurality of side apertures, inserting a locking element through said external aperture and said one of said plurality of side apertures, and locking a prop lock in place; wherein, said lower portion comprises said prop having said lower exterior portion, said upper interior portion, and said prop lock; and said one or more fixed beam-head prop assemblies comprise said lower portion having a central fixed beam-head shaft, an upper portion having said threaded shaft, said threaded collar.

14. The method of using an improved grid shoring system of claim 13, further comprising: attaching a screw-jack threaded shaft assembly to a drop-head comprises: aligning a plurality of fastening apertures of a bottom plate of said drop-head with a plurality of fastening apertures of an upper attachment plate of said screw-jack threaded shaft assembly, and inserting and locking one or more nut and bolt assemblies through said plurality of fastening apertures in said bottom plate and said upper attachment plate; and wherein, said upper portion comprises said drop-head and said screw-jack threaded shaft assembly, and said drop-head comprises said bottom plate having said plurality of fastening apertures.

15. The method of using an improved grid shoring system of claim 13, further comprising: forming said improved grid shoring system with said one or more fixed beam-head prop assemblies by: adjusting a height of each among said one or more fixed beam-head prop assemblies,

13

arranging said one or more fixed beam-head prop assemblies,  
 attaching said one or more fixed beam-head prop assemblies to one another with said one or more beams, and  
 attaching one or more panels to said one or more beams.  
 16. An improved grid shoring system comprising:  
 one or more fixed beam-head prop assemblies supporting one or more beams;  
 each of said one or more fixed beam-head prop assemblies comprise an upper portion, a lower portion, a variable height, and a threaded collar;  
 said upper portion having a screw-jack threaded shaft assembly;  
 said screw-jack threaded shaft assembly comprises a threaded shaft having an external diameter and an external threading and  
 an upper attachment plate having a plurality of fastening apertures;  
 said upper portion of said one or more fixed beam-head prop assemblies selectively slide into said lower portion of said one or more fixed beam-head prop assemblies;  
 said threaded collar comprises an internal threading and an internal diameter;  
 said internal threading of said threaded collar rotateably attaches to said external threading of said screw-jack threaded shaft assembly of said upper portion;  
 said lower portion comprises a lower central shaft having an internal diameter being larger than said external diameter of said threaded shaft;

14

said upper portion and said lower portion adjustably attach to one another by  
 selectively sliding said threaded shaft in an up and down direction through said lower central shaft of said lower portion, and  
 vertically adjusting said threaded collar along said threaded shaft to select said variable height;  
 said upper portion comprises a first end cap seat;  
 said lower portion comprises a second end cap seat;  
 said upper portion comprises a drop-head;  
 said drop-head comprises a bottom plate having a plurality of fastening apertures;  
 said screw-jack threaded shaft assembly attaches to said drop-head by  
 aligning said plurality of fastening apertures of said bottom plate of said drop-head with said plurality of fastening apertures of said upper attachment plate of said screw-jack threaded shaft assembly, and  
 inserting and locking one or more nut and bolt assemblies through said plurality of fastening apertures in said bottom plate and said upper attachment plate;  
 said first end cap seat is selectively attached to said drop-head of said upper portion;  
 said first end cap seat comprises a variable height; and  
 adjusting said variable height of said first end cap seat comprises adjusting said threaded collar between said upper portion and said lower portion of said one or more fixed beam-head prop assemblies.

\* \* \* \* \*