



US011498138B2

(12) **United States Patent**
Dunivan

(10) **Patent No.:** **US 11,498,138 B2**
(45) **Date of Patent:** **Nov. 15, 2022**

(54) **BANDSAW AUTOMATED PORTIONING SAW SYSTEM AND METHOD OF USE**

(71) Applicant: **Steve Dunivan**, Amarillo, TX (US)

(72) Inventor: **Steve Dunivan**, Amarillo, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 141 days.

(21) Appl. No.: **16/751,100**

(22) Filed: **Jan. 23, 2020**

(65) **Prior Publication Data**

US 2020/0230722 A1 Jul. 23, 2020

Related U.S. Application Data

(60) Provisional application No. 62/796,027, filed on Jan. 23, 2019.

(51) **Int. Cl.**

B23D 55/04 (2006.01)

A22C 17/00 (2006.01)

(52) **U.S. Cl.**

CPC **B23D 55/046** (2013.01); **A22C 17/002** (2013.01)

(58) **Field of Classification Search**

CPC B23D 55/046; A22C 17/002; B26D 1/56
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,499,124 A * 6/1924 Reichmann B23D 55/046
83/421
3,832,929 A * 9/1974 Pedi B23D 55/10
83/714

4,442,741 A * 4/1984 Whittingham B26D 1/547
83/110
4,534,085 A * 8/1985 Stewart A22C 25/16
452/161
4,583,435 A * 4/1986 Fessler B26D 7/01
83/277
5,117,717 A * 6/1992 Maliy B26D 5/20
53/157
5,324,228 A * 6/1994 Vogeley, Jr. A22C 17/0086
452/150
5,364,302 A * 11/1994 Shibata A22C 7/00
452/174

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2511345 A1 * 7/2004 B26D 7/30
CA 2947594 A1 * 5/2017 B23D 55/043

(Continued)


Primary Examiner — Sean M Michalski

(74) *Attorney, Agent, or Firm* — Shannon Warren

(57) **ABSTRACT**

An automated saw for assessing an uncut meat and calculating one or more of a cut depth and cutting one or more cut portions. The automated saw comprises a bandsaw blade, a controller, a visual sensor and a meat positioning assembly. The controller comprises a computer comprising an address space, and a processor, a memory. The controller stores a device application in the memory and runs the device application on the processor. The meat positioning assembly comprises a pusher and a tray configured to move the uncut meat relative to the bandsaw blade. The tray is configured to hold the uncut meat. The pusher is configured to slide the uncut meat through the tray. The meat positioning assembly is configured to move the tray in a forward direction and a rearward direction relative to the bandsaw blade.

6 Claims, 12 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,482,166 A * 1/1996 Brown A22C 17/002
209/939
5,492,502 A * 2/1996 Hjorth A22C 25/142
452/170
5,974,925 A * 11/1999 Lindee B26D 1/0006
83/403.1
6,070,509 A * 6/2000 Lonn B26D 1/62
83/318
6,152,004 A * 11/2000 Nispel B26D 7/32
83/155
6,640,681 B1 * 11/2003 Weber B26D 7/18
83/27
6,935,215 B2 * 8/2005 Lindee B26D 7/0683
83/74
7,073,419 B2 * 7/2006 Weber B26D 7/01
83/14
7,603,936 B2 * 10/2009 Pryor B26D 7/01
83/277
7,621,806 B2 * 11/2009 Bottemiller A22C 17/008
452/150
8,408,108 B2 * 4/2013 Redemann B26D 1/143
83/356
8,893,599 B2 * 11/2014 Reifenhaeuser B26D 7/32
83/23
9,764,490 B2 * 9/2017 Weber B26D 7/30
9,950,869 B1 * 4/2018 Pryor B65G 23/44
9,981,400 B2 * 5/2018 Dreier B65H 35/08
10,160,602 B2 * 12/2018 Torrenga B65G 15/12
10,639,798 B2 * 5/2020 Pryor B26D 7/01
10,703,001 B2 * 7/2020 Einloft-Velte B65H 20/32
10,751,899 B2 * 8/2020 Lischinski B26D 1/143
10,751,900 B2 * 8/2020 Einloft-Velte B65H 35/08
10,829,335 B2 * 11/2020 Gerhardt B65H 20/02
2002/0083816 A1 * 7/2002 Krauss B26D 7/01
83/932
2003/0145700 A1 * 8/2003 Lindee B26D 7/32
83/29
2003/0221532 A1 * 12/2003 Long B23D 55/046
83/651

2005/0085176 A1 * 4/2005 Houtz A22C 17/0086
452/157
2005/0132855 A1 * 6/2005 Weber B26D 9/00
83/155
2005/0132863 A1 * 6/2005 Biggs A22C 17/0013
83/788
2006/0156878 A1 * 7/2006 Faires B65G 47/31
83/13
2007/0157776 A1 * 7/2007 Sorensen A22C 17/0086
83/23
2009/0145272 A1 * 6/2009 Sandberg B26D 7/18
83/13
2010/0206143 A1 * 8/2010 Lin B23D 55/046
82/127
2011/0126680 A1 * 6/2011 Weber B26D 7/2635
83/13
2012/0167730 A1 * 7/2012 Schaub B26D 7/32
83/39
2013/0139664 A1 * 6/2013 Diehr B26D 7/01
83/37
2014/0356086 A1 * 12/2014 Hirko B23B 41/02
408/69
2015/0205288 A1 * 7/2015 Strong A22C 17/002
700/114
2017/0165858 A1 * 6/2017 Bochtler B26D 7/0683
2017/0266831 A1 * 9/2017 Wachter B26D 7/0625
2017/0368707 A1 * 12/2017 Keller B26D 7/0633
2018/0111283 A1 * 4/2018 Klockow B26D 7/2614
2018/0169888 A1 * 6/2018 Weber B26D 7/0616
2018/0186022 A1 * 7/2018 Fox A22C 17/002
2019/0061027 A1 * 2/2019 Stolzer B23D 55/088
2019/0232513 A1 * 8/2019 Erne B26D 7/0616
2019/0281843 A1 * 9/2019 Volkl B26D 7/01
2020/0288729 A1 * 9/2020 Blaine G05B 17/02
2020/0315191 A1 * 10/2020 Hofmann A22C 17/0093
2021/0227840 A1 * 7/2021 Blaine A22C 17/002

FOREIGN PATENT DOCUMENTS

DE 102017112177 A1 * 12/2018 B26D 3/161
EP 3238898 A1 * 11/2017 B26D 7/01
EP 3831559 A1 * 6/2021 A22C 7/0046
WO WO-0013864 A1 * 3/2000 B23D 55/046

* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11A




FIG. 11B



FIG. 12

1

BANDSAW AUTOMATED PORTIONING SAW SYSTEM AND METHOD OF USE

CROSS-REFERENCE TO RELATED APPLICATIONS

Not applicable.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT (IF APPLICABLE)

Not applicable.

REFERENCE TO SEQUENCE LISTING, A TABLE, OR A COMPUTER PROGRAM LISTING COMPACT DISC APPENDIX (IF APPLICABLE)

Not applicable.

BACKGROUND OF THE INVENTION

No prior art is known to the Applicant

BRIEF SUMMARY OF THE INVENTION

An automated saw for assessing an uncut meat and calculating one or more of a cut depth and cutting one or more cut portions. Said automated saw comprises a bandsaw blade, a controller, a visual sensor and a meat positioning assembly. Said meat positioning assembly comprises a pusher and a tray configured to move said uncut meat relative to said bandsaw blade. Said tray is configured to hold said uncut meat. Said pusher is configured to slide said uncut meat through said tray. Said meat positioning assembly is configured to move said tray in a forward direction and a rearward direction relative to said bandsaw blade. Said uncut meat comprises a first end and a second end. Said first end of said uncut meat comprises a surface area and a diameter. Said uncut meat comprises an uncut meat weight. Said one or more cut portions comprise at least a first cut portion of said uncut meat. Said controller is configured for calculating a fraction comprising a cut portion weight divided by said uncut meat weight and multiplying said fraction with an uncut meat length to determine said cut depth, activating said meat positioning assembly to align a cutting plane at said cut depth from said first end, cutting said first cut portion from said uncut meat with said bandsaw blade, and repeating these steps as required to separate said one or more cut portions from said uncut meat.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

FIG. 1 illustrates a network diagram 102.

FIGS. 2A, 2B, 2C, 2D and 2E illustrate a mobile phone 200a, a personal computer 200b, a tablet 200c, a smart watch 200d and a smart phone 200e, respectively.

FIGS. 3A, 3B and 3C illustrate an address space 302, an address space 302a and an address space 302e, respectively.

FIGS. 4A and 4B illustrate a flow chart between said one or more computers 106 and said server 108.

FIGS. 5A and 5B illustrate interactions between a device application 502, a server application 506 and said data storage 110.

FIG. 6 illustrates a perspective overview of an automated saw 600.

2

FIG. 7 illustrates an elevated top view of said automated saw 600.

FIG. 8 illustrates an isometric overview of said uncut meat 702 on said tray 618.

FIG. 9 illustrates a perspective overview of said meat positioning assembly 614 and an uncut meat weight 904.

FIG. 10 illustrates an elevated front view of said tray 618.

FIGS. 11A and 11B illustrate an overview and block diagram view of a back-side of said automated saw 600 with a cutting plane 1110 being calculated.

FIG. 12 illustrates a method of use 1200 of said automated saw 600.

DETAILED DESCRIPTION OF THE INVENTION

The following description is presented to enable any person skilled in the art to make and use the invention as claimed and is provided in the context of the particular examples discussed below, variations of which will be readily apparent to those skilled in the art. In the interest of clarity, not all features of an actual implementation are described in this specification. It will be appreciated that in the development of any such actual implementation (as in any development project), design decisions must be made to achieve the designers' specific goals (e.g., compliance with system- and business-related constraints), and that these goals will vary from one implementation to another. It will also be appreciated that such development effort might be complex and time-consuming, but would nevertheless be a routine undertaking for those of ordinary skill in the field of the appropriate art having the benefit of this disclosure. Accordingly, the claims appended hereto are not intended to be limited by the disclosed embodiments, but are to be accorded their widest scope consistent with the principles and features disclosed herein.

FIG. 1 illustrates a network diagram 102.

In one embodiment, said network diagram 102 can comprise one or more computers 106, one or more locations 104, and a network 112. In one embodiment, said one or more locations 104 can comprise a first location 104a, a second location 104b and a third location 104c. Said one or more computers 106 can comprise a first computer 106a, a second computer 106b, a wearable computer 106c, a wearable computer 106d and a third computer 106e. In one embodiment, a server 108 can communicate with said one or more computers 106 over said network 112. Said one or more computers 106 can be attached to a printer 114 or other accessories, as is known in the art.

In one embodiment, said server 108 can attach to a data storage 110.

In one embodiment, said printer 114 can be hardwired to said first computer 106a (not illustrated here), or said printer 114 can connect to one of said one or more computers 106 (such as said second computer 106b, as illustrated) via said network 112.

Said network 112 can be a local area network (LAN), a wide area network (WAN), a piconet, or a combination of LANs, WANs, or piconets. One illustrative LAN is a network within a single business. One illustrative WAN is the Internet.

In one embodiment, said server 108 represents at least one, but can be many servers, each connected to said network 112. Said server 108 can connect to said data storage 110. Said data storage 110 can connect directly to said server 108, as shown in FIG. 1, or may exist remotely on said network 112. In one embodiment, said data storage

110 can comprise any suitable long-term or persistent storage device and, further, may be separate devices or the same device and may be collocated or distributed (interconnected via any suitable communications network).

FIGS. 2A, 2B, 2C, 2D and 2E illustrate a mobile phone 200a, a personal computer 200b, a tablet 200c, a smart watch 200d and a smart phone 200e, respectively.

In one embodiment, said one or more computers 106 can comprise said mobile phone 200a, said personal computer 200b, said tablet 200c, said smart watch 200d or said smart phone 200e. In one embodiment, each among said one or more computers 106 can comprise one or more input devices 204, a keyboard 204a, a trackball 204b, one or more cameras 204c, a track pad 204d, a data 206 and/or a home button 220, as is known in the art.

In the last several years, the useful definition of a computer has become more broadly understood to include mobile phones, tablet computers, laptops, desktops, and similar. For example, Microsoft®, have attempted to merge devices such as a tablet computer and a laptop computer with the release of “Windows® 8”. In one embodiment, said one or more computers each can include, but is not limited to, a laptop (such as said personal computer 200b), desktop, workstation, server, mainframe, terminal, a tablet (such as said tablet 200c), a phone (such as said mobile phone 200a), and/or similar. Despite different form-factors, said one or more computers can have similar basic hardware, such as a screen 202 and said one or more input devices 204 (such as said keyboard 204a, said trackball 204b, said one or more cameras 204c, a wireless—such as RFID—reader, said track pad 204d, and/or said home button 220). In one embodiment, said screen 202 can comprise a touch screen. In one embodiment, said track pad 204d can function similarly to a computer mouse as is known in the art. In one embodiment, said tablet 200c and/or said personal computer 200b can comprise a Microsoft® Windows® branded device, an Apple® branded device, or similar. In one embodiment, said tablet 200c can be an X86 type processor or an ARM type processor, as is known in the art.

Said network diagram 100 can comprise said data 206. In one embodiment, said data 206 can comprise data related to financial transactions.

In one embodiment, said one or more computers can be used to input and view said data 206. In one embodiment, said data 206 can be input into said one or more computers by taking pictures with one of said one or more camera 204c, by typing in information with said keyboard 204a, or by using gestures on said screen 202 (where said screen 202 is a touch screen). Many other data entry means for devices like said one or more computers are well known and herein also possible with said data 206. In one embodiment, said first computer 102a can comprise an iPhone®, a BlackBerry®, a smartphone, or similar. In one embodiment, one or more computers can comprise a laptop computer, a desktop computer, or similar.

FIGS. 3A, 3B and 3C illustrate an address space 302, an address space 302a and an address space 302e, respectively.

In one embodiment, said one or more computers 106 can comprise said address space 302, and more specifically, said first computer 106a can comprise said address space 302a, said second computer 106b can comprise an address space 302b, said wearable computer 106c can comprise an address space 302c, said wearable computer 106d can comprise an address space 302d; and said server 108 can comprise said address space 302e. In turn, each among said address space 302 can comprise a processor 304, a memory 306, a communication hardware 308 and a location hardware 310.

Thus, said address space 302a a processor 304a, a memory 306a, a communication hardware 308a and a location hardware 310a; said address space 302b can comprise a processor 304b, a memory 306b, a communication hardware 308b and a location hardware 310b; said address space 302c can comprise a processor 304c, a memory 306c, a communication hardware 308c and a location hardware 310c; said address space 302d can comprise a processor 304d, a memory 306d, a communication hardware 308d and a location hardware 310d; and said address space 302e can comprise a processor 304e, a memory 306e, a communication hardware 308e and a location hardware 310e.

Each among said one or more computers 106 and said server 108 can comprise an embodiment of said address space 302. In one embodiment, said processor 304 can comprise a plurality of processors, said memory 306 can comprise a plurality of memory modules. In one embodiment, said data 206 can be sent to said processor 304; wherein, said processor 304 can perform processes on said data 206 according to an application stored in said memory 306, as discussed further below. Said processes can include storing said data 206 into said memory 306, verifying said data 206 conforms to a one or more preset standards, or ensuring a required set among said required said data 206 has been gathered for said data management system and method. In one embodiment, said data 206 can include data which said one or more computers 106 can populate automatically, such as a date and a time, as well as data entered manually. Once a portion of gathering data has been performed said data 206 can be communicated over said network 112. The network can include a network transport processor for packetizing data, communication ports for wired communication, or an antenna for wireless communication. In one embodiment, said data 206 can be collected in one or more computers and delivered to said server 108 through said network 112.

FIGS. 4A and 4B illustrate a flow chart between said one or more computers 106 and said server 108.

In the first embodiment, said communication hardware 308a and said communication hardware 308e can send and receive said data 206 to and from one another and or can communicate with said data storage 110 across said network 112. Likewise, in the second embodiment, said data storage 110 can be embedded inside of said one or more computers 106, which may speed up data communications over said network 112.

As illustrated in FIG. 4A, in one embodiment, said server 108 can comprise a third-party data storage and hosting provider or privately managed as well.

As illustrated in FIG. 4B, a data storage 110a can be located on said first computer 106a. Thus, said first computer 106a can operate without a data connection out to said server 108.

FIGS. 5A and 5B illustrate interactions between a device application 502, a server application 506 and said data storage 110.

For nomenclature, each among data records can comprise a set of data records in use on said one or more computers 106; thus said first computer 106a can comprise a data records 504a, said second computer 106b can comprise a data records 504b, said wearable computer 106c can comprise a data records 504c, and said wearable computer 106d can comprise a data records 504d.

FIG. 6 illustrates a perspective overview of an automated saw 600.

In one embodiment, said automated saw 600 can comprise a base 602, a conveyor 604, a post 606, an overhang

5

portion **608**, a controller **610**, a visual sensor **612**, a meat positioning assembly **614**, a pusher **616**, a tray **618** and a bandsaw blade **620**. Said base **602** can comprise a lower portion of said automated saw **600** which supports said tray **618** and said meat positioning assembly **614**. In one embodiment, said meat positioning assembly **614** can comprise a system which moves said tray **618** and said pusher **616** relative to other portions of said automated saw **600**. In one embodiment, said conveyor **604** can transport elements having been cut by said bandsaw blade **620**, as discussed below. In one embodiment, said visual sensor **612** can comprise a camera, as is known in the art. In one embodiment, said tray **618** can move in two or three axes as dictated by said controller **610**.

In one embodiment, said controller **610** can comprise one among said one or more computers **106**. In one embodiment, said controller **610** can receive signals from said visual sensor **612**, said meat positioning assembly **614**, others among said one or more computers **106** and/or said server **108** to determine movement of said meat positioning assembly **614** and movement of said bandsaw blade **620**.

Said controller **610** can comprise one among said one or more computers **106** comprising said address space **302**, said processor **304**, said memory **306** and said communication hardware **308**. Said controller **610** can be store said device application **502** in said memory **306** and run said device application **502** on said processor **304** as discussed above and known in the art.

FIG. 7 illustrates an elevated top view of said automated saw **600**.

One objective of said automated saw **600** can be to control movement of an uncut meat **702** within a forward direction **708** and a rearward direction **706**; with the added control of movement of said uncut meat **702** relative to said tray **618** by pressing said uncut meat **702** with said pusher **616** in said forward direction **708**.

FIG. 8 illustrates an isometric overview of said uncut meat **702** on said tray **618**.

FIG. 9 illustrates a perspective overview of said meat positioning assembly **614** and an uncut meat weight **904**.

In one embodiment, said automated saw **600** can comprise a scale **900**. In one embodiment, said controller **610** can communicate with said scale **900** to determine said uncut meat weight **904** of said uncut meat **702** at a given time. In one embodiment, said controller **610** can be configured to calculate said uncut meat weight **904** before and after cutting with said bandsaw blade **620**.

In one embodiment, said tray **618** can comprise two sides **902** (which can comprise a first side **902a** and a second side **902b**). said first side **902a** and said second side **902b** can be arranged in a "V" shape with a lower join line **906** forming a substantially straight line at the point they meet.

FIG. 10 illustrates an elevated front view of said tray **618**.

FIGS. 11A and 11B illustrate an overview and block diagram view of a back-side of said automated saw **600** with a cutting plane **1110** being calculated.

In one embodiment, said automated saw **600** can calculate a diameter **1100**, a surface area **1102** and a cut depth **1104** of said uncut meat **702**. As a starting point, said automated saw **600** can know an uncut meat length **1112**, said diameter **1100** and said uncut meat weight **904** of said uncut meat **702**. It can thereby calculate said cutting plane **1110** by using said surface area **1102** and said cut depth **1104** along with said uncut meat weight **904**, said diameter **1100** and said uncut meat length **1112** to determine where to place said cutting plane **1110** to cut one or more cut portions **1114**.

6

In one embodiment, said one or more cut portions **1114** can comprise at least a first cut portion **1114a** and a second cut portion **1114b**. Further, said one or more cut portions **1114** can comprise a cut portion weight **1116**.

As illustrated, said automated saw **600** has already cut said first cut portion **1114a**, and has calculated said uncut meat length **1112** from said uncut meat weight **904** and said uncut meat length **1112** by dividing the desired quantity of said cut portion weight **1116** for said second cut portion **1114b** by said uncut meat weight **904**, then taking that fraction and multiplying it by said uncut meat length **1112**, the product of which comprises said cut depth **1104**.

In another embodiment, said cut depth **1104** can be calculated by accounting for said surface area **1102** where said uncut meat **702** is not consistently the same width as said diameter **1100**; wherein, said cut depth **1104** can be calculated by accounting for a volume and/or density of said uncut meat **702** along the entirety of said uncut meat length **1112**.

FIG. 12 illustrates a method of use **1200** of said automated saw **600**.

Said method of use **1200** can comprise a starting step **1202a**, a calculation steps **1202b**, an application steps **1202c** and a status assessment step **1202d**, as illustrated and discussed herein.

Said automated saw **600** for assessing said uncut meat **702** and calculating one or more of said cut depth **1104** and cutting said one or more cut portions **1114**. Said automated saw **600** comprises said bandsaw blade **620**, said controller **610**, said visual sensor **612** and said meat positioning assembly **614**. Said meat positioning assembly **614** comprises said pusher **616** and said tray **618** configured to move said uncut meat **702** relative to said bandsaw blade **620**. Said tray **618** can be configured to hold said uncut meat **702**. Said pusher **616** can be configured to slide said uncut meat **702** through said tray **618**. Said meat positioning assembly **614** can be configured to move said tray **618** in said forward direction **708** and said rearward direction **706** relative to said bandsaw blade **620**. Said uncut meat **702** comprises a first end **1106** and a second end **1108**. Said first end **1106** of said uncut meat **702** comprises said surface area **1102** and said diameter **1100**. Said uncut meat **702** comprises said uncut meat weight **904**. Said one or more cut portions **1114** comprise at least said first cut portion **1114a** of said uncut meat **702**. Said controller **610** can be configured for calculating a fraction comprising said cut portion weight **1116** divided by said uncut meat weight **904** and multiplying said fraction with said uncut meat length **1112** to determine said cut depth **1104**, activating said meat positioning assembly **614** to align said cutting plane **1110** at said cut depth **1104** from said first end **1106**, cutting said first cut portion **1114a** from said uncut meat **702** with said bandsaw blade **620**, and repeating these steps as required to separate said one or more cut portions **1114** from said uncut meat **702**.

Said automated saw **600** for assessing said uncut meat **702** and calculating one or more of said cut depth **1104** and cutting said one or more cut portions **1114**. Said automated saw **600** comprises said bandsaw blade **620**, said controller **610**, said visual sensor **612** and said meat positioning assembly **614**. Said meat positioning assembly **614** selectively pushes said uncut meat **702** relative to said bandsaw blade **620**. Said meat positioning assembly **614** can be configured to move said tray **618** in said forward direction **708** and said rearward direction **706** relative to said bandsaw blade **620**. Said uncut meat **702** comprises said first end **1106** and said second end **1108**. Said first end **1106** of said uncut meat **702** comprises said surface area **1102** and said diameter

1100. Said uncut meat 702 comprises said uncut meat weight 904. Said one or more cut portions 1114 comprise at least said first cut portion 1114a of said uncut meat 702. Said controller 610 can be configured for calculating said cut depth 1104 of said uncut meat 702 in order to yield said cut portion weight 1116 being a desired cut portion of said uncut meat 702, activating said meat positioning assembly 614 to align said cutting plane 1110 at said cut depth 1104 from said first end 1106, cutting said first cut portion 1114a from said uncut meat 702 with said bandsaw blade 620 along said cutting plane 1110, and repeating these steps as required to separate said one or more cut portions 1114 from said uncut meat 702.

calculating said cut depth 1104 of said uncut meat 702 comprises calculating a fraction comprising said cut portion weight 1116 divided by said uncut meat weight 904 and multiplying said fraction with said uncut meat length 1112 to determine said cut depth 1104.

Said meat positioning assembly 614 comprises said pusher 616 and said tray 618 configured to move said uncut meat 702 relative to said bandsaw blade 620. Said tray 618 can be configured to hold said uncut meat 702. Said pusher 616 can be configured to slide said uncut meat 702 through said tray 618.

cutting said first cut portion 1114a from said uncut meat 702 with said bandsaw blade 620 along said cutting plane 1110 comprises pushing said uncut meat 702 with said pusher 616 to said cut depth 1104 being a distance equal to a depth of said first cut portion 1114a, and aligning said cutting plane 1110 with said cut depth 1104.

Various changes in the details of the illustrated operational methods are possible without departing from the scope of the following claims. Some embodiments may combine the activities described herein as being separate steps. Similarly, one or more of the described steps may be omitted, depending upon the specific operational environment the method is being implemented in. It is to be understood that the above description is intended to be illustrative, and not restrictive. For example, the above-described embodiments may be used in combination with each other. Many other embodiments will be apparent to those of skill in the art upon reviewing the above description. The scope of the invention should, therefore, be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled. In the appended claims, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein.”

The invention claimed is:

1. An automated saw for assessing an uncut meat and calculating one or more of a cut depth and cutting one or more cut portions, wherein:

- said automated saw comprises a bandsaw blade, a controller, a visual sensor and a meat positioning assembly;
- said controller comprises a computer comprising an address space, and a processor, a memory;
- said controller stores a device application in said memory and runs said device application on said processor;

said meat positioning assembly comprises a pusher and a tray configured to move said uncut meat relative to said bandsaw blade;

said tray is configured to hold said uncut meat;

said pusher is configured to slide said uncut meat through said tray;

said meat positioning assembly is configured to move said tray in a forward direction and a rearward direction relative to said bandsaw blade;

said uncut meat comprises a first end and a second end;

said first end of said uncut meat comprises a surface area and a diameter;

said uncut meat comprises an uncut meat weight;

said controller is configured, with said device application, for:

- assessing said uncut meat with said visual sensor and a scale,
- calculating a volume and density of said uncut meat along the entirety of an uncut meat length of said uncut meat,
- calculating, given weight of a desired cut portion, a fraction comprising said desired cut portion divided by said uncut meat weight,
- calculating a portion of said uncut meat comprising a volume associated with said fraction of said desired cut portion divided by said uncut meat weight,
- calculating a location for determine said cut depth,
- activating said meat positioning assembly to align a cutting plane at said cut depth from said first end, and cutting a portion from said uncut meat with said bandsaw blade.

2. The automated saw of claim 1, wherein: said visual sensor comprises a camera.

3. The automated saw of claim 1, wherein: said tray is configured to move in two or three axes as dictated by said controller.

4. The automated saw of claim 1, wherein: said device application in said controller is configured for receiving signals from said visual sensor, said meat positioning assembly, determining movement of said meat positioning assembly, and operating of said bandsaw blade.

5. The automated saw of claim 1, wherein: said automated saw comprises said scale;

said controller is configured to communicate with said scale to determine said uncut meat weight of said uncut meat at a given time; and

said controller is configured to calculate said uncut meat weight before and after cutting with said bandsaw blade.

6. The automated saw of claim 1, wherein: said tray comprises a first side and a second side; and said first side and said second side is arranged in a “V” shape with a lower join line forming a substantially straight line at the point they meet.

* * * * *