



US009538861B2

(12) **United States Patent**
Young et al.

(10) **Patent No.:** **US 9,538,861 B2**
(45) **Date of Patent:** **Jan. 10, 2017**

(54) **STORAGE SYSTEM**

(71) Applicant: **Happy Gal, LLC**, Panhandle, TX (US)

(72) Inventors: **Julie Young**, Panhandle, TX (US);
Roger Hayes, Amarillo, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/827,247**

(22) Filed: **Aug. 14, 2015**

(65) **Prior Publication Data**

US 2016/0045040 A1 Feb. 18, 2016

Related U.S. Application Data

(60) Provisional application No. 62/037,210, filed on Aug. 14, 2014.

(51) **Int. Cl.**

A47F 5/05 (2006.01)

A47F 5/02 (2006.01)

A47F 5/04 (2006.01)

A47F 5/08 (2006.01)

A47B 51/00 (2006.01)

(52) **U.S. Cl.**

CPC . **A47F 5/05** (2013.01); **A47F 5/02** (2013.01);
A47F 5/04 (2013.01); **A47F 5/08** (2013.01);
A47B 2051/005 (2013.01)

(58) **Field of Classification Search**

CPC **A47F 5/05**; **A47F 5/06**; **A47F 5/02**;
A47F 5/04; **A47F 5/0823**; **A47F**
5/08; **A47B 47/00**; **A47B 47/0066**; **A47B**
49/004; **A47B 51/00**; **A47B 55/00**; **A47B**
85/00
USPC **211/107**, **168**, **174**, **190**, **194**, **205**; **312/108**,
125, **126**, **351.2**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,101,849 A * 6/1914 Hines A47B 11/00
108/95
1,610,534 A 12/1926 Rice et al.
1,929,677 A * 10/1933 Davis A47B 77/16
312/202
2,326,064 A * 8/1943 Pittman A47B 49/004
211/163
2,941,669 A * 6/1960 Palay A47B 96/1425
211/1.55
3,570,412 A 3/1971 Holman et al.
3,635,352 A * 1/1972 Brooks A47F 5/05
211/168
3,998,334 A * 12/1976 Smith A47F 7/16
211/163
4,232,790 A * 11/1980 Serrano G11B 33/0466
211/163

(Continued)

FOREIGN PATENT DOCUMENTS

CA 20002314439 7/2000
CN 202653807 U 1/2013

OTHER PUBLICATIONS

<https://www.google.com/patents/US20070080120?dq=US20070080120A1&hl=en&sa=X&ei=YA-WU9D-E8O2yAT42oCIBg&ved=0CCkQ6wEwAA>.

(Continued)



Primary Examiner — James O Hansen

(74) Attorney, Agent, or Firm — Shannon L Warren

(57) **ABSTRACT**

A storage system comprising an inner rod, an outer body, an upper foot, a lower foot, and a one or more pegs. Said outer body rotatably attaches to said inner rod. Said upper foot and said lower foot press against a ceiling and a ground surface. Said inner rod comprises a tension rod having a variable length. Said one or more pegs extend out from said outer body.

18 Claims, 32 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,838,625	A *	6/1989	Taylor		A47B 61/00	211/163
5,033,626	A *	7/1991	Platti		A47B 49/004	211/163
5,127,528	A *	7/1992	Cone		A47B 96/1425	211/163
5,318,175	A *	6/1994	Stevens		A47G 25/0664	211/107
5,330,061	A	7/1994	Geltz			
5,482,237	A	1/1996	Wang			
6,568,546	B1 *	5/2003	Huang		A47B 49/00	211/205
7,946,543	B2 *	5/2011	Cotter		A47B 61/00	211/1.53
8,408,405	B2	4/2013	Yang et al.			
2007/0080120	A1	4/2007	Greiner			
2013/0037503	A1	2/2013	Cimino et al.			

OTHER PUBLICATIONS

<https://www.jossandmain.com/The-Organized-Closet-Hinton-Corner-Valet~WES1032~E10029.html>.

https://www.google.com/search?q=site:jossandmain.com+shoe+tree&newwindow=1&es_sm=93&source=lnms&tbm=isch&sa=X&ei=J95HU5jpFsmG8QHfhYCwDQ&ved=0CAkQ_AUoAg&biw=1288&bih=774#facrc=&imgre=s8vczRiJcNYGWM%253A%3B6ZCE9CCR-1S3oM%3Bhttps%253A%252F%252Fsecure.img.josscdn.com%252Fflf%252F53%252Fhash%252F8447%252F10099525%252F1%252FDiva%25252BShoe%25252BTree.jpg%3Bhttps%0253A%252F%252Fwww.jossandmain.com%252FBest-of-2013%25253A-Organization-Benson-Shoe-Tree~HIXK1080~E8348.html%3B450%3B450.

* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3A






FIG. 3B






FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 6




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 9




FIG. 10




FIG. 11A




FIG. 11B




FIG. 12




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 14




FIG. 15A




FIG. 15B




FIG. 16




FIG. 17




FIG. 18A




FIG. 18B




FIG. 18C




FIG. 19A




FIG. 19B




FIG. 19C




FIG. 20




FIG. 21A




FIG. 21B




FIG. 21C




FIG. 21D




FIG. 22A

FIG. 22B




FIG. 22C




FIG. 23A




FIG. 24A




FIG. 24B




FIG. 25A




FIG. 25B




FIG. 25C




FIG. 26




FIG. 27




FIG. 28A




FIG. 28B




FIG. 29A




FIG. 29B




FIG. 30




FIG. 31




FIG. 32

1

STORAGE SYSTEM**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application claims benefit of U.S. Patent Application No. 62/037,210 (filed 2014 Aug. 14), which is hereby incorporated by reference.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT (IF APPLICABLE)

Not applicable.

REFERENCE TO SEQUENCE LISTING, A TABLE, OR A COMPUTER PROGRAM LISTING COMPACT DISC APPENDIX (IF APPLICABLE)

Not applicable.

BACKGROUND OF THE INVENTION

This disclosure relates generally to a storage system. A few examples of such systems can be found in various patent records and include these record numbers: CN202653807U, US 20130037503 A1, CA20002314439 20000721, U.S. Pat. No. 1,610,534 A, U.S. Pat. No. 5,482,237 A, U.S. Pat. No. 3,570,412 A, U.S. Pat. No. 8,408,405 B2, U.S. Pat. No. 5,330,061 A, and US 20070080120 A1.

None of the above inventions and patents, taken either singularly or in combination, is seen to describe the instant disclosure as claimed. Accordingly, an improved storage system would be advantageous.

BRIEF SUMMARY OF THE INVENTION

A storage system and method of use are disclosed.

Said storage system comprising an inner rod, an outer body, an upper foot, a lower foot, and a one or more pegs. Said outer body rotatably attaches to said inner rod. Said upper foot and said lower foot press against a ceiling and a ground surface. Said inner rod comprises a tension rod having a variable length. Said one or more pegs extend out from said outer body.

A method of manufacturing a storage system comprising: manufacturing a storage system comprising of a one or more storage segments of an outer body, a one or more pegs, an inner rod, an upper foot, a lower foot, and a top segment. Said outer body rotatably attaches to said inner rod. Said upper foot and said lower foot press against a ceiling and a ground surface. Said inner rod comprises a tension rod having a variable length. Said one or more pegs extend out from said outer body.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

FIG. 1 illustrates a perspective overview of a storage system.

FIGS. 2A and 2B illustrate a perspective front overview and an elevated front view of said storage system.

FIGS. 3A and 3B illustrate a perspective front overview and an elevated front view of a second embodiment of said storage system, referred to as a storage system.

FIGS. 4A and 4B illustrate a perspective exploded overview of said top segment with said upper foot and a

2

perspective cross-section assembled overview of said top segment with said upper foot.

FIGS. 5A, 5B and 5C illustrate one solid line view and two wireframe views of said first segment; comprising a perspective overview in solid line, an elevated front view in wireframe, and a perspective wireframe overview in wireframe.

FIG. 5D illustrates an exploded perspective overview of said first segment and said second segment with said first setscrew.

FIG. 6 illustrates a perspective cross-section overview of an upper portion of said storage system.

FIGS. 7A and 7B illustrate an elevated cross-section front view and a perspective cross-section overview of said inner rod.

FIGS. 8A and 8B illustrate two elevated front views of said storage system (sans said outer body); wherein said FIG. 8A illustrates said storage system in a first height and said FIG. 8B illustrates said storage system in a second height.

FIG. 9 illustrates an elevated top view of said first segment, a cross-section of said inner rod, a short peg and a long peg.

FIG. 10 illustrates a perspective overview of one embodiment of a storage system.

FIGS. 11A and 11B illustrate a perspective front overview of said storage system and said storage system with a one or more pegs.

FIG. 12 illustrates a perspective front overview of said storage system.

FIGS. 13A, 13B and 13C illustrate a perspective front overview, an elevated top view of said first storage segment of said storage system, and an elevated wireframe front view of said first segment.

FIG. 14 illustrates a perspective cross-section overview of said first segment and said second segment attached to one another.

FIGS. 15A and 15B illustrate an elevated front side view and an elevated front side cross-section view of said inner rod with said upper foot, said lower foot and said top segment.

FIG. 16 illustrates an elevated exploded front side view of said storage system sans one or more storage segments.

FIG. 17 illustrates a perspective front side cross-section view of said lower foot and said second rod.

FIG. 18A illustrates a perspective view of said lower foot.

FIG. 18B illustrates an elevated top view of said lower foot.

FIG. 18C illustrates an elevated side view of said lower foot.

FIG. 19A illustrates a perspective view of said upper foot.

FIG. 19B illustrates a top elevated view of said upper foot.

FIG. 19C illustrates an elevated side view of said upper foot.

FIG. 20 is a perspective front side view of said top segment, said first segment, said inner rod, and said upper foot.

FIG. 21A illustrates a perspective view of a poster hanger assembly.

FIG. 21B is a side elevated view of said poster hanger assembly.

FIG. 21C illustrates the front elevated view of the poster hanger assembly.

FIG. 21D illustrates the rear elevated view of the poster hanger assembly.

FIG. 22A illustrates a side elevated view of said poster hanger assembly.

3

FIG. 22B illustrates an elevated view of said first segment before said poster hanger assembly fits into said first segment.

FIG. 22C illustrates an elevated view of said poster hanger assembly latched on inserted into said first segment.

FIG. 23A illustrates a perspective view of FIG. 22C, showing said poster hanger assembly inserted into said first segment.

FIG. 24A is an elevated view of said one or more storage segments such as first segment.

FIG. 24B is a top elevated view of a one or more storage segments of said outer body such as said first segment.

FIG. 25A illustrates a side elevated view and a front cross-section elevated view of a peg assembly.

FIG. 25B illustrates an elevated front view of said first large aperture with a cross-section view of said peg assembly there-through.

FIG. 25C illustrates a second hook assembly of common knowledge that may fit in a peg board.

FIG. 26 illustrates an exploded perspective overview of a first segment 2600a.

FIG. 27 illustrates a perspective overview of said storage system 100 with said first segment 2600a and said second segment 2600b.

FIGS. 28A and 28B illustrate a perspective overview of said first segment 2600a and a portion thereof.

FIGS. 29A and 29B illustrate a first side and a second side perspective overview of said storage system 1000.

FIG. 30 illustrates a perspective overview of a portion of said storage system 1000.

FIG. 31 illustrates an exploded perspective overview of said three side panel enclosure 2606 and said mail compartment 2902.

FIG. 32 illustrates a perspective overview of said compartment 2704.

DETAILED DESCRIPTION OF THE INVENTION

Described herein is a storage system. The following description is presented to enable any person skilled in the art to make and use the invention as claimed and is provided in the context of the particular examples discussed below, variations of which will be readily apparent to those skilled in the art. In the interest of clarity, not all features of an actual implementation are described in this specification. It will be appreciated that in the development of any such actual implementation (as in any development project), design decisions must be made to achieve the designers' specific goals (e.g., compliance with system- and business-related constraints), and that these goals will vary from one implementation to another. It will also be appreciated that such development effort might be complex and time-consuming, but would nevertheless be a routine undertaking for those of ordinary skill in the field of the appropriate art having the benefit of this disclosure. Accordingly, the claims appended hereto are not intended to be limited by the disclosed embodiments, but are to be accorded their widest scope consistent with the principles and features disclosed herein.

FIG. 1 illustrates a perspective overview of a storage system 100. In one embodiment, said storage system 100 can comprise an inner rod 102, an outer body 104, an upper foot 106a, and a lower foot 106b. In one embodiment, said outer body 104 can comprise a top segment 107 and a one or more storage segments. In one embodiment, said one or more storage segments can comprise a first segment 108a, a

4

second segment 108b, a third segment 108c, a fourth segment 108d, and a fifth segment 108e. In one embodiment, said one or more storage segments attach to one another, as described below. In one embodiment, said one or more storage segments attach to said top segment 107. In one embodiment, said top segment 107 can attach to a portion of said inner rod 102 and/or said upper foot 106a.

In one embodiment, said inner rod 102 can comprise a tension rod, capable of being releasably attached between a ceiling 110 and a ground surface 112. In one embodiment, said upper foot 106a can create a friction surface between said storage system 100 and said ceiling 110, and said lower foot 106b can create a friction surface between said storage system 100 and said ground surface 112.

Said storage system 100 can be placed in a setting to display store garments. Said setting can be a retail store. A use for said storage system 100 can be to hang one or more of a t-shirt, a hat, a pair of jeans, a sweater, a pair of pants, an undergarment, and an article of clothing for display. Said storage system 100 can be used to display said hung clothing to perspective customers.

FIGS. 2A and 2B illustrate a perspective front overview and an elevated front view of said storage system 100. In one embodiment, said outer body 104 can comprise a plurality of apertures (such as a first aperture 204a and a second aperture 204b) which can receive and hold a one or more pegs (which can comprise a first peg 202a and a second peg 202b). In one embodiment, said one or more pegs can receive garments such as hats, shirts, or other items which a user of said storage system 100 may wish to hang there upon.

In one embodiment, at least two of storage segments as illustrated by 108a, 108b, 108c, 108d, and 108e, can be stacked one on top of another said storage segment.

In one embodiment, said storage system 100 can comprise a plurality of setscrews (such as a first setscrew 220a, a second setscrew 220b, and a top set screw 220z); wherein, said plurality of setscrews can attach each of said one or more storage segments to one another. For example, in one embodiment, said first segment 108a and said second segment 108b can be releasably attached to one another with said first setscrew 220a. In one embodiment, said plurality of setscrews can be allocated one per junction 222 between said one or more storage segments, and one between said first segment 108a (that is the top most among said one or more storage segments and said top segment 107).

FIGS. 3A and 3B illustrate a perspective front overview and an elevated front view of a second embodiment of said storage system 100, referred to as a storage system 300. In one embodiment, said storage system 300 can be substantially similar to said storage system 100, but-for replacing said outer body 104 of said storage system 100 with an integrated outer body 304. In one embodiment, said integrated outer body 304 can comprise a single piece of molded plastic (or other material, as known in the art). Accordingly, said storage system 300 can comprise said storage system 100 without using said one or more storage segments.

FIGS. 4A and 4B illustrate a perspective exploded overview of said top segment 107 with said upper foot 106a and a perspective cross-section assembled overview of said top segment 107 with said upper foot 106a. In one embodiment, said upper foot 106a can comprise a neck portion 406 and a lower portion 408. In one embodiment, said lower portion 408 can comprise a bell-shape having a first diameter 420 at said neck portion 406 and a second diameter 422 at the bottom of said lower portion 408; wherein, said second diameter 422 is larger than said first diameter 420a. In one embodiment, said top segment 107 can comprise a neck

5

aperture **410** (having a neck aperture diameter **424**). In one embodiment, said storage system **100** can comprise a central vertical axis **430**. In one embodiment, rotatably attaching said top segment **107** to said upper foot **106a** can comprise aligning each with said central vertical axis **430**; sliding a portion of said neck portion **406** through said neck aperture **410**; and resting a portion of an internal surface **432** of said top segment **107** on said lower portion **408**. In one embodiment, said top segment **107** and said upper foot **106a** can rotate relative to one another along said internal surface **432**; thus, said upper foot **106a** can remain fixed relative to said ceiling **110** and allow said top segment **107** and said outer body **104** (attached to it) to spin about said internal surface **432**. In one embodiment, said top segment **107** can comprise an inner threading **440**.

In one embodiment, said upper foot **106a** can comprise a socket **450**.

FIGS. **5A**, **5B** and **5C** illustrate one solid line view and two wireframe views of said first segment **108a**; comprising a perspective overview in solid line, an elevated front view in wireframe, and a perspective wireframe overview in wireframe. In one embodiment, said one or more storage segments can all have similar specifications to said first segment **108a**, as illustrated. In one embodiment, said **108a** can comprise a base portion **502** and a socket portion **504**; wherein, said base portion **502** screws into said socket portion **504**. In one embodiment, said first segment **108a** can comprise an inner surface **506**, an outer surface **508**, an outer threading **510**, an inner threading **512**, and a one or more side apertures (which can comprise a first side aperture **514a**, a second side aperture **514b**, a third side aperture **514c** and a fourth side aperture **514d**). In one embodiment, said outer threading **510** of a first among said one or more storage segments can attach to said inner threading **512** of a second among said one or more storage segments. In one embodiment, said outer surface **508** of said one or more storage segments can comprise a round or cylindrical shape. In one embodiment, said one or more side apertures can be arranged in said outer surface **508** of said one or more storage segments, as illustrated.

FIG. **5D** illustrates an exploded perspective overview of said first segment **108a** and said second segment **108b** with said first setscrew **220a**. In one embodiment, said one or more storage segments can each comprise an inner setscrew socket **520** and an outer setscrew socket **522**. In one embodiment, said plurality of setscrews can attach a first segment (such as said first segment **108a**) to a second segment (such as said second segment **108b**) of said one or more storage segments to one another by: screwing said base portion **502** of said second segment **108b** into said socket portion **504** of said first segment **108a**; aligning said outer setscrew socket **522** of said first segment **108a** with an inner setscrew socket **520b** of said second segment **108b**; and screwing one among said plurality of setscrews (such as said first setscrew **220a**) through said outer setscrew socket **522** of said first segment **108a** and into said inner setscrew socket **520b** of said second segment **108b**.

FIG. **6** illustrates a perspective cross-section overview of an upper portion of said storage system **100**. In one embodiment, said outer body **104** can rotate around said central vertical axis **430** around said inner rod **102**. In one embodiment, each among said one or more storage segments can releasably attach to one another with a procedure similar to the following procedure as between said first segment **108a** and said second segment **108b**: aligning said one or more storage segments around said central vertical axis **430** and around said inner rod **102**; screwing a outer threading **510b**

6

of said second segment **108b** into an inner threading **512a** of said first segment **108a**; and inserting said first setscrew **220a** (not illustrated here) as described above. Likewise, said first segment **108a** can releasably attach to said top segment **107** by: screwing an outer threading **510a** of said first segment **108a** into said inner threading **440** of said top segment **107**; and setting said top set screw **220z** through a portion of said top segment **107** and said first segment **108a** (not illustrated here).

In one embodiment, said inner rod **102** can comprise an upper end **602**. In one embodiment, said upper end **602** can slide into said socket **450**.

In one embodiment, said upper foot **106a** can comprise a top surface **650**. In one embodiment, said top surface **650** can be on top of said neck portion **406**. In one embodiment, said top surface **650** can comprise a high friction material like rubber, thereby securing said upper foot **106a** to said ceiling **110** when an upward force is applied to said upper foot **106a**.

FIGS. **7A** and **7B** illustrate an elevated cross-section front view and a perspective cross-section overview of said inner rod **102**. In one embodiment, said inner rod **102** can comprise a first rod **702a** and a second rod **702b**. In one embodiment, said first rod **702a** screws into said second rod **702b**. In one embodiment, said first rod **702a** can comprise an outer threading **704a** and said second rod **702b** can comprise an inner threading **704b**. In one embodiment, said outer threading **704a** can screw into said inner threading **704b**.

FIGS. **8A** and **8B** illustrate two elevated front views of said storage system **100** (sans said outer body **104**); wherein said FIG. **8A** illustrates said storage system **100** in a first height **802** and said FIG. **8B** illustrates said storage system **100** in a second height **804**. In one embodiment, said inner rod **102** can comprise an adjustable height allowing said storage system **100** to have a variable height between said ceiling **110** and said ground surface **112**. For example, by adjusting said first rod **702a** and said second rod **702b** by twisting said outer threading **704a** and said inner threading **704b** relative to one another, said adjustable height can be selectively changed between said first height **802** and said second height **804**.

FIG. **9** illustrates an elevated top view of said first segment **108a**, a cross-section of said inner rod **102**, a short peg **902** and a long peg **904**. In one embodiment, said short peg **902** and said long peg **904** can attach to said one or more storage segments as illustrated, or as described below. A full range of pegs and accessories can be used with said storage system **100** as one in the art would understand.

FIG. **10** illustrates a perspective overview of one embodiment of a storage system **1000**. In one embodiment, said storage system **1000** can comprise an inner rod **102**, an outer body **1004**, an upper foot **106a**, and a lower foot **106b**. In one embodiment, said outer body **1004** can comprise a top segment **1007** and a one or more storage segments. In one embodiment, said one or more storage segments can comprise a first segment **1008a**, a second segment **1008b**, a third segment **1008c**, a fourth segment **1008d**, and a fifth segment **1008e**. In one embodiment, said storage segments are at least one of: a cube, a rectangular cube, a box, a cuboid, and a cylinder. In one embodiment, said one or more storage segments attach to one another, as described below. In one embodiment, said one or more storage segments attach to said top segment **1007**. In one embodiment, said top segment **1007** can attach to a portion of said inner rod **102** and/or said upper foot **106a**. In one embodiment, a clothing hanger **1012** can attach to said storage system **1000**. Said

clothing hanger **1012** can have a shirt **1014** or other articles of clothing hung on it as is generally known.

In one embodiment, said inner rod **102** can comprise a tension rod, capable of being releasably attached between a ceiling **110** and a ground surface **112**. In one embodiment, said upper foot **106a** can create a friction surface between said storage system **1000** and said ceiling **110**, and said lower foot **106b** can create a friction surface between said storage system **1000** and said ground surface **112**.

A use for said storage system **1000** can be to hang one or more of a t-shirt, said shirt **1014**, a hat, a pair of jeans, a sweater, a pair of pants, an undergarment, and an article of clothing for display. Said storage system **1000** can be used to display said hung clothing to perspective customers.

FIGS. **11A** and **11B** illustrate a perspective front overview of said storage system **1000** and said storage system **1000** with a one or more pegs. In one embodiment, said outer body **1004** can comprise a plurality of apertures (which can comprise a plurality of large apertures and a plurality of small apertures), which can receive and hold at least one of: a peg (described and illustrated below) a hook (described and illustrated below), and a clothing hanger **1012**. In one embodiment, said plurality of large apertures can comprise a first large aperture **1102a**, a second large aperture **1102b**, and a third large aperture **1102c**. In one embodiment, said plurality of small apertures can comprise a first small aperture **1104a**, a second small aperture **1104b**, and a third small aperture **1104c**.

In one embodiment, a portion of said plurality of apertures can comprise a peg board **1110**. In one embodiment, said peg board **1110** can comprise said plurality of small apertures.

In one embodiment, said storage system **1000** can comprise a plurality of pegs capable of releasably attaching to said plurality of apertures. In one embodiment, said plurality of pegs can comprise a one or more large pegs and a one or more small pegs. In one embodiment, said one or more large pegs can fit in said plurality of large apertures, and said one or more small pegs can fit in said plurality of small apertures. In one embodiment, said one or more large pegs can comprise a first large peg **1122a** and said one or more small pegs can comprise a first small peg **1124a**, as illustrated.

In one embodiment, at least two of said one or more storage segments can be releasably stacked and attached to one another. In one embodiment, a highest storage segment (which can comprise said first segment **1008a**) connects to said top segment **1007**.

FIG. **12** illustrates a perspective front overview of said storage system **1000**. In one embodiment said outer body **1004** of said storage system **1000** rotates horizontally. In one embodiment at least one storage segment among said one or more storage segments can rotate about a central vertical axis **1202**. In one embodiment, a rotating force that causes said outer body **1004** to rotate originates from a user's hand. In one embodiment, a rotating force that causes at least one of said one or more storage segments to rotate originates from a user. In one embodiment, said one or more storage segments can attach to one another in an aligned configuration (as in FIG. **11**) or in a non-aligned configuration (as illustrated here in FIG. **12**); wherein, said non-aligned configuration indicates that at least one among said one or more storage segments has an exterior planar surface which is not substantially parallel with other exterior planar surfaces of said one or more storage segments.

In one embodiment, said outer body **1004** rotates about said central vertical axis **1202** relative to said lower foot **106b** and or said upper foot **106a**.

In one embodiment, said top segment **1007** can releasably attach to said first segment **1008a**. In one embodiment, said top segment **1007** can rotate along with said first segment **1008a** relative to said central vertical axis **1202**.

FIGS. **13A**, **13B** and **13C** illustrate a perspective front overview, an elevated top view of said first storage segment **1008a** of said storage system **1000**, and an elevated wire-frame front view of said first segment **1008a**. In one embodiment, said first storage segment **1008a** can comprise a base portion **1302**, a threaded portion **1304**, an outer surface **1306**, an inner surface **1308**, said plurality of apertures, and a socket **1322** having an internal threading **1324**.

In one embodiment, said first segment **1008a** comprises a first side panel **1320a**, a second side panel **1320b**, a third side panel **1320c**, and a fourth side panel **1320d**. In one embodiment said first side panel **1320a**, second side panel **1320b**, third side panel **1320c**, and fourth side panel **1320d** can comprise congruent parts.

In one embodiment, attaching said one or more storage segments to one another comprises screwing said threaded portion **1304** of a lower segment in to said socket **1322** of an upper segment. In one embodiment, said one or more storage segments can comprise said plurality of setscrews as discussed above (but not illustrated here, as their functionality is substantially identical).

FIG. **14** illustrates a perspective cross-section overview of said first segment **1008a** and said second segment **1008b** attached to one another. In one embodiment, each among said one or more storage segments can comprise a central support (such as a central support **1402a** for said first segment **1008a** and a central support **1402b** for said second segment **1008b**). In one embodiment, said central supports can wrap around a portion of said inner rod **102** and provide horizontal stability of said one or more storage segments relative to said inner rod **102**.

FIGS. **15A** and **15B** illustrate an elevated front side view and an elevated front side cross-section view of said inner rod **102** with said upper foot **106a**, said lower foot **106b** and said top segment **1007**.

FIG. **16** illustrates at elevated exploded front side view of said storage system **1000** sans one or more storage segments.

FIG. **17** illustrates a perspective front side cross-section view of said lower foot **106b** and said second rod **702b**. In one embodiment, said second rod **702b** can comprise a lower end **1704**. In one embodiment, said lower foot **106b** can comprise a socket **1702**. In one embodiment, said lower end **1704** can slide into said socket **1702** and secure a lower portion of said inner rod **102**. In one embodiment, said lower foot **106b** can comprise a bottom surface **1706** which can comprise a high friction material like rubber, thereby securing said storage system **1000** (or said storage system **100**) to said ground surface **112**.

FIG. **18A** illustrates a perspective view of said lower foot **106b**. FIG. **18B** illustrates an elevated top view of said lower foot **106b**. FIG. **18C** illustrates an elevated side view of said lower foot **106b**. In one embodiment, said lower foot **106b** comprises a top surface **1802**, a lower surface **1804**, and said socket **1702**.

In one embodiment, said top surface **1802** can have a dome shape. In one embodiment, said lower surface **1804** can have a flat bottom. In one embodiment, said socket **1702** can be placed on the vertex of said top surface **1802**. In one embodiment, said lower foot **106b** can comprise a puck shaped lower surface and a dome like top surface. In one embodiment, said lower foot **106b** can comprise a flat lower surface and a dome shaped upper surface. In one embodiment said lower foot **106b** can comprise a flat lower surface

and a geometric shaped upper surface including, but not limited to, a cube, rectangular cube, a prism, and related shapes.

FIG. 19A illustrates a perspective view of said upper foot **106a**. FIG. 19B illustrates a top elevated view of said upper foot **106a**. FIG. 19C illustrates an elevated side view of said upper foot **106a**. Said upper foot **106a** comprises a neck portion **406**, an upper surface **1904**, and a lower surface **1906**. In one embodiment, said neck portion **406** can comprise a cylindered shape. In one embodiment, said neck portion **406** can comprise at least one of the following: a cube, a rectangular cube, a prism, and a geometric shape. In one embodiment, said upper surface **1904** can comprise a dome shape. In one embodiment, said lower surface **1906** can comprise a flat surface.

FIG. 20 is a perspective front side view of said top segment **1007**, said first segment **1008a**, said inner rod **102**, and said upper foot **106a**. In one embodiment, said top segment **1007** can comprise an outer surface **2002**, and an internal threading **2004** in a socket **2006**. In one embodiment, said outer surface **2002** can comprise a square base **2008**. In one embodiment, said socket **2006** can releasably hold one among said one or more storage segments. For example, in one embodiment, said first segment **1008a** can attach to said top segment **1007** by screwing said threaded portion **1304** of said base portion **1302** into said internal threading **2004** of said socket **2006**.

FIG. 21A illustrates a perspective view of a poster hanger assembly **2100**. In one embodiment said poster hanger assembly comprises a front side **2102**, a back side **2110**, at least one curved peg **2112**, an upper fold **2106a**, and a lower fold **2106b**. In one embodiment, said poster hanger assembly comprises a first curved peg **2104a** and a second curved peg **2104b**.

FIG. 21B is a side elevated view of said poster hanger assembly **2100**. In one embodiment, said upper fold **2106a** can comprise an 'L' shape fold. Said lower fold **2106b** can comprise an L shape fold. In one embodiment, said upper fold **2106a** can comprise a curve shape. In one embodiment, said lower fold **2106b** can comprise a curve shape. In one embodiment a poster **2108** can slide into said poster hanger assembly **2100**. In one embodiment, said poster **2108** can be at least one of the following: a flyer, a written document, a cardboard sheet, a plastic sheet, and a thin rectangular object. In one embodiment, said upper fold **2106a** and lower fold **2106b** prevent said poster **2108** from moving vertically.

FIG. 21C illustrates the front elevated view of the poster hanger assembly **2100**.

FIG. 21D illustrates the rear elevated view of the poster hanger assembly **2100**. In one embodiment said poster hanger assembly has a back side **2110**. In one embodiment, said first curved peg **2104a** and said second curved peg **2104b** latch on to the back side **2110** of poster hanger assembly **2100**.

FIG. 22A illustrates a side elevated view of said poster hanger assembly **2100**. Said back side **2110** of said poster hanger assembly **2100** attaches to said first segment **1008a**. In one embodiment said poster hanger assembly attaches to said one or more storage segments.

FIG. 22B illustrates an elevated view of said first segment **1008a** before said poster hanger assembly **2100** fits into said first segment **1008a**. In one embodiment, said poster hanger assembly **2100** attaches to said one or more storage segments.

FIG. 22C illustrates an elevated view of said poster hanger assembly **2100** latched on inserted into said first segment **1008a**. In one embodiment, said poster hanger

assembly attaches to said first segment **1008a** when said first curved peg **2104a** and second curved peg **2104b** are inserted into one or more of said first large aperture **1102a**. In one embodiment, said curved portion ### of said first curved peg **2104a** and second curved peg **2104b** prevent said poster hanger assembly **2100** from coming out of said first segment **1008a** unless said poster hanger assembly is lifted and tilted to allow said curved portion ### to slide out said first large aperture **1102a**. In one embodiment said poster hanger assembly **2100** can fit into any segments of said outer body **104**.

FIG. 23A illustrates a perspective view of FIG. 22C, showing said poster hanger assembly **2100** inserted into said first segment **1008a**.

FIG. 24A is an elevated view of said one or more storage segments such as first segment **1008a**.

FIG. 24B is a top elevated view of a one or more storage segments of said outer body **1004** such as said first segment **1008a**. Said first segment **1008a** can comprise a threaded portion **1304**, an outer surface **1306**, said inner surface **1308**, and said central support **1402a**. In one embodiment said plate may have an aperture **2404**. In one embodiment, said aperture **2404** can be fitted around said inner rod **102**. In one embodiment, said central support **1402a** can comprise a rectangular side **2406** with an oblong center portion **2408**. In one embodiment, said oblong center portion **2408** can comprise an oval shape.

FIG. 25A illustrates a side elevated view and a front cross-section elevated view of a peg assembly **2500**. In one embodiment, said **2500** can attach to one of said plurality of apertures (which can comprise one among said first large aperture **1102a**, said second large aperture **1102b** and/or said third large aperture **1102c**). In one embodiment, said peg assembly **2500** can comprise an inner portion **2502** which can comprise a portion held within said segment and an outer portion **2504** which can comprise a portion held outside of said segment.

In one embodiment, said hook assembly comprises a hook **2502** and an end **2504**. In one embodiment, said hook **2502** can be inserted into said first large aperture **1102a** in said outer body **1004** of said storage system **1000**, holding said hook **2502** in place. In one embodiment, said end can be a curved peg. In one embodiment, said curved end can be used to hang articles of clothing. In one embodiment, said hook assembly **2500** can be used in multiple apertures. In one embodiment, multiple said hook assembly **2500** systems can be used to uniquely hang any object that can be hung.

FIG. 25B illustrates an elevated front view of said first large aperture **1102a** with a cross-section view of said peg assembly **2500** there-through. In one embodiment, said peg assembly **2500** can comprise an oval or elliptical shaped cross-section being similar to the shape of said first large aperture **1102a** and a little smaller in dimensions. Accordingly, said peg assembly **2500** can pass through said plurality of apertures (such as said first large aperture **1102a**) but may be prohibited from rotating about a central horizontal axis **2520**.

FIG. 25C illustrates a second hook assembly **2504** of common knowledge that may fit in a peg board.

FIG. 26 illustrates an exploded perspective overview of a first segment **2600a**.

In one embodiment, said first segment **2600a** can comprise one among said one or more storage segments.

In one embodiment, said first segment **2600a** can comprise a top surface **2602**, a bottom surface **2604**, a three side panel enclosure **2606** (comprising of said first side panel **1320a**, said second side panel **1320b**, and said third side

11

panel **1320c**), said fourth side panel **1320d**, a lower spacer **2608**, and an upper spacer **2610**.

As illustrated, said bottom surface **2604** of said first segment **2600a** can selectively mate with an upper surface **2602b** of a second segment **2600b**.

In one embodiment, said plurality of side panels can comprise said first side panel **1320a**, said second side panel **1320b**, said third side panel **1320c**, and said fourth side panel **1320d**. In one embodiment, said three side panel enclosure **2606** can be used without said fourth side panel **1320d** to form said plurality of side panels. In one embodiment, said lower spacer **2608** and/or said upper spacer **2610** can be used to center said one or more storage segments around said inner rod **102**. In one embodiment, said bottom surface **2604** can mate with said top surface **2602**.

FIG. 27 illustrates a perspective overview of said storage system **100** with said first segment **2600a** and said second segment **2600b**.

In one embodiment, said second segment **2600b** (as with all among said one or more storage segments) can comprise a gasket **2702** on said top surface **2602** for cushion and grip between said one or more storage segments.

In one embodiment, said one or more storage segments can comprise a two or more storage segments, where said storage system **100** and/or said storage system **1000** require more than one segment for implementation.

In one embodiment, said one or more storage segments can comprise a compartment **2704** between said top surface **2602** and said bottom surface **2604**. In one embodiment, said compartment **2704** can be partially enclosed by said plurality of side panels. In one embodiment, said compartment **2704** can be partially enclosed by said three side panel enclosure **2606**.

FIGS. 28A and 28B illustrate a perspective overview of said first segment **2600a** and a portion thereof.

FIGS. 29A and 29B illustrate a first side and a second side perspective overview of said storage system **1000**.

In one embodiment, said storage system **1000** can comprise said first segment **2600a**, said second segment **2600b**, and a third segment **2600c**. In one embodiment, said one or more storage segments can comprise said fourth side panel **1320d**, a mail compartment **2902**, and/or said compartment **2704**.

In one embodiment, said mail compartment **2902** can comprise a plurality of slots **2904** for receiving mail parcels, as is known in the art.

In one embodiment, said three side panel enclosure **2606** can comprise a first corner panel **2920a** and a second corner panel **2920b**, as illustrated.

FIG. 30 illustrates a perspective overview of a portion of said storage system **1000**.

In one embodiment, said lower spacer **2608** can comprise a portion of said one or more storage segments that ensure said one or more storage segments remain centered on said inner rod **102**, as is known in the art and illustrated.

FIG. 31 illustrates an exploded perspective overview of said three side panel enclosure **2606** and said mail compartment **2902**.

FIG. 32 illustrates a perspective overview of said compartment **2704**.

Various changes in the details of the illustrated operational methods are possible without departing from the scope of the following claims. Some embodiments may combine the activities described herein as being separate steps. Similarly, one or more of the described steps may be omitted, depending upon the specific operational environment the method is being implemented in. It is to be

12

understood that the above description is intended to be illustrative, and not restrictive. For example, the above-described embodiments may be used in combination with each other. Many other embodiments will be apparent to those of skill in the art upon reviewing the above description. The scope of the invention should, therefore, be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled. In the appended claims, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein.”

The invention claimed is:

1. A storage system comprising:

a storage system having an inner rod, an outer body and a lower foot;

said inner rod selectively attaches to said lower foot;

said outer body comprising two or more storage segments;

said inner rod comprising a substantially cylindrical shape, being aligned with a central vertical axis;

said two or more storage segments selectively slide over said inner rod;

said two or more storage segments are configured to rotate around said inner rod;

said two or more storage segments comprise a first segment and a second segment;

said two or more storage segments each comprise

a top surface,

a bottom surface,

a plurality of side panels,

a base portion on said top surface or bottom surface, and

a socket portion being across from said base portion in said top surface or bottom surface;

said top surface of said two or more storage segments releaseably mate with said bottom surface of another among said two or more storage segments;

said storage system further comprises an upper foot; wherein, said upper foot is configured to press against a ceiling;

said lower foot is configured to press against a ground surface;

said inner rod comprises a tension rod having a variable length;

said inner rod comprises a first rod and a second rod;

said first rod comprises an outer threading;

said second rod comprises an inner threading;

said first rod selectively screws into said second rod so as to alter a length of said inner rod between said ground surface and said ceiling;

segments comprise a substantially cubical shape;

said plurality of side panels comprise at least a first side panel, a second side panel, a third side panel, and a fourth side panel;

said plurality of side panels comprise at least one side being open to expose a storage compartment between the others among said plurality of side panels, said bottom surface and said top surface;

said two or more storage segments comprise at least one of plastic, wood, ceramic, glass, metal, and biological material;

said socket portion comprising a female threading,

said base portion comprising a male threading; and

said top surface of said two or more storage segments is configured to releaseably mate with said bottom surface of another among said two or more storage segments by

13

threading said male threading of said base into said female threading of said socket.

2. A storage system comprising:
 a storage system having an inner rod, an outer body and a lower foot; 5
 said inner rod selectively attaches to said lower foot;
 said outer body comprising two or more storage segments;
 said inner rod comprising a substantially cylindrical shape, being aligned with a central vertical axis; 10
 said two or more storage segments selectively slide over said inner rod;
 said two or more storage segments are configured to rotate around said inner rod;
 said two or more storage segments comprise a first 15
 segment and a second segment;
 said two or more storage segments each comprise
 a top surface,
 a bottom surface, 20
 a plurality of side panels,
 a base portion on said top surface or bottom surface, and
 a socket portion being across from said base portion in said top surface or bottom surface;
 said top surface of said two or more storage segments 25
 releaseably mate with said bottom surface of another among said two or more storage segments;
 said storage system further comprises an upper foot wherein,
 said upper foot is configured to press against a ceiling; 30
 said lower foot is configured to press against a ground surface; and
 said inner rod comprises a tension rod having a variable length;
 said inner rod comprises a first rod and a second rod; 35
 said first rod comprises an outer threading;
 said second rod comprises an inner threading; and
 said first rod selectively screws into said second rod so as to alter a length of said inner rod between said ground surface and said ceiling. 40

3. The storage system of claim 2 wherein:
 said two or more storage segments comprise a substantially cubical shape; and
 said plurality of side panels comprise at least a first side panel, a second side panel, a third side panel, and a 45
 fourth side panel.

4. The storage system of claim 2 wherein: said plurality of side panels comprise at least a first side panel, a second side panel, and a third side panel; said plurality of side panels are enclosed on three sides at-a-said first side panel, said second 50
 side panel and said third side panel, but remains open at a fourth side of said two or more storage segments; and said fourth side being open to expose a storage compartment between the others among said plurality of side panels, said bottom surface and said top surface. 55

5. The storage system of claim 4 wherein:
 said fourth side configured to selectively receive a fourth side panel.

6. The storage system of claim 2 wherein:
 said plurality of side panels comprise at least one side 60
 being open to expose a storage compartment between the others among said plurality of side panels, said bottom surface and said top surface.

7. The storage system of claim 2 wherein:
 said storage system further comprises one or more pegs; 65
 and
 said one or more pegs extend out from said outer body.

14

8. The storage system of claim 7 wherein:
 said outer body comprises a pegboard comprising one or more apertures in said plurality of side panels;
 said pegboard comprise an array of apertures arranged for receiving said one or more pegs, and
 said one or more pegs selectively attach to said one or more apertures.

9. The storage system of claim 2 wherein:
 said two or more storage segments are configured to receive a set screw to prevent rotary movement of said outer body.

10. The storage system of claim 2 wherein:
 said two or more storage segments comprise at least one of plastic, wood, ceramic, glass, metal, and biological material.

11. The storage system of claim 2 wherein:
 said socket portion comprising a female threading, said base portion comprising a male threading; and
 said top surface of said two or more storage segments is configured to releaseably mate with said bottom surface of another among said two or more storage segments by threading said male threading of said base into said female threading of said socket.

12. The storage system of claim 2 wherein: said storage system further comprises a top segment; wherein, a portion of said inner rod releaseably attaches to said upper foot; a portion of said two or more storage segments attach to said top segment; said top segment couples with and rotates about said upper foot; and said outer body rotates with said top segment.

13. The storage system of claim 2 wherein:
 said bottom surface of said two or more storage segments comprises a central support comprising a center aperture being wrapped close to said inner rod; and
 said outer body rotates around said inner rod with said central support configured to support said outer body from substantial lateral movement.

14. The storage system of claim 13 wherein:
 said central support comprises an intermediate spacer configured to rest between a lower aperture in said bottom surface of an upper segment in said two or more storage segments and a lower segment in said two or more storage segments.

15. A method of manufacturing a storage system comprising:
 manufacturing a storage system comprising two or more storage segments of an outer body, one or more pegs, an inner rod, an upper foot, a lower foot, and a top segment; wherein,
 said outer body rotatably attaches to said inner rod;
 said upper foot and said lower foot press against a ceiling and a ground surface;
 said inner rod comprises a tension rod having a variable length;
 said one or more pegs extend out from said outer body;
 said inner rod selectively attaches to said lower foot
 said inner rod comprising a substantially cylindrical shape, being aligned with a central vertical axis;
 said two or more storage segments selectively slide over said inner rod;
 said two or more storage segments are configured to rotate around said inner rod;
 said two or more storage segments comprise a first segment and a second segment
 said two or more storage segments each comprise
 a top surface,
 a bottom surface,

15

a plurality of side panels,
 a base portion on said top surface or bottom surface,
 and
 a socket portion being across from said base portion in
 said top surface or bottom surface;
 said top surface of said two or more storage segments
 releaseably mate with said bottom surface of another
 among said two or more storage segments;
 said storage system further comprises an upper foot
 wherein,
 said upper foot is configured to press against a ceiling;
 said lower foot is configured to press against a ground
 surface; and
 said inner rod comprises a tension rod having a variable
 length;
 said inner rod comprises a first rod and a second rod;
 said first rod comprises an outer threading;
 said second rod comprises an inner threading; and
 said first rod selectively screws into said second rod so as
 to alter a length of said inner rod between said ground
 surface and said ceiling.
16. A storage system comprising:
 a storage system having an inner rod, an outer body and
 a lower foot;
 said inner rod selectively attaches to said lower foot;
 said outer body comprising a two or more storage seg-
 ments;
 said inner rod comprising a substantially cylindrical
 shape, being aligned with a central vertical axis;
 said two or more storage segments selectively slide over
 said inner rod;
 said two or more storage segments are configured to rotate
 around said inner rod;
 said two or more storage segments comprise a first
 segment and a second segment;
 said two or more storage segments each comprise
 a top surface,
 a bottom surface,
 a plurality of side panels,
 a base portion on said top surface or bottom surface,
 and
 a socket portion being across from said base portion in
 said top surface or bottom surface;
 said top surface of said two or more storage segments
 releaseably mate with said bottom surface of another
 among said two or more storage segments;
 said socket portion comprising a female threading, said
 base portion comprising a male threading; and
 said top surface of said two or more storage segments is
 configured to releaseably mate with said bottom surface

16

of another among said two or more storage segments by
 threading said male threading of said base into said
 female threading of said socket.
17. A storage system comprising:
 a storage system having an inner rod, an outer body and
 a lower foot;
 said inner rod selectively attaches to said lower foot;
 said outer body comprising two or more storage seg-
 ments;
 said inner rod comprising a substantially cylindrical
 shape, being aligned with a central vertical axis;
 said two or more storage segments selectively slide over
 said inner rod;
 said two or more storage segments are configured to rotate
 around said inner rod;
 said two or more storage segments comprise a first
 segment and a second segment;
 said two or more storage segments each comprise
 a top surface,
 a bottom surface,
 a plurality of side panels,
 a base portion on said top surface or bottom surface,
 and
 a socket portion being across from said base portion in
 said top surface or bottom surface;
 said top surface of said two or more storage segments
 releaseably mate with said bottom surface of another
 among said two or more storage segments;
 said plurality of side panels comprise at least a first side
 panel, a second side, and a third side;
 said plurality of side panels are enclosed on three sides at
 a said first side panel, said second side panel and said
 third side panel, but remains open at a fourth side of
 said two or more storage segments;
 said fourth side being open to expose a storage compart-
 ment between the others among said plurality of side
 panels, said bottom surface and said top surface;
 said storage compartment comprises an empty volume
 within said storage segments;
 said empty volume substantially fills a space defined by
 three of said plurality of side panels on its sides, said
 top surface above and said bottom surface below; and
 said storage compartment is configured to selectively
 receive items for storage within said storage segment.
18. The storage system of claim 17 wherein: said storage
 system comprises a plurality of said storage compartments;
 said plurality of said storage compartment can be partially
 enclosed by said storage segments; said plurality of said
 storage compartments are configured for storing items.

* * * * *