

(12) **United States Patent**
Miller

(10) **Patent No.: US 11,130,438 B2**
(45) **Date of Patent: Sep. 28, 2021**

(54) **PROPANE TANK TIE DOWN SYSTEM AND METHOD OF USE**

(71) Applicant: **Heath Miller**, Round Rock, TX (US)

(72) Inventor: **Heath Miller**, Round Rock, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 78 days.

(21) Appl. No.: **16/586,922**

(22) Filed: **Sep. 28, 2019**

(65) **Prior Publication Data**

US 2021/0094461 A1 Apr. 1, 2021

(51) **Int. Cl.**

B60P 7/08 (2006.01)

B60P 7/12 (2006.01)

B60P 7/135 (2006.01)

F17C 13/08 (2006.01)

(52) **U.S. Cl.**

CPC **B60P 7/0823** (2013.01); **B60P 7/0807** (2013.01); **B60P 7/12** (2013.01); **B60P 7/135** (2013.01); **F17C 13/084** (2013.01); **F17C 2201/0104** (2013.01); **F17C 2221/035** (2013.01)

(58) **Field of Classification Search**

CPC B60P 7/0807; B60P 7/065; B60P 7/0823; B60P 7/12; B60P 7/135; B60Y 2410/132

USPC 410/96, 106

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

852,623 A * 5/1907 Roth A62B 1/14 182/7
1,396,270 A * 11/1921 Grierson F41C 33/001 224/150

2,563,698 A * 8/1951 Whitebread A47G 29/093 248/499
3,120,403 A * 2/1964 Molzan B66C 1/18 294/74
3,998,367 A * 12/1976 Harding F41B 5/1461 224/625
4,878,274 A * 11/1989 Patricy A44B 18/00 24/306
4,918,790 A * 4/1990 Cirket A44B 11/006 24/442
5,063,641 A * 11/1991 Chuan A44B 11/18 24/197
5,083,692 A * 1/1992 Treese A45F 3/15 224/615
5,092,505 A * 3/1992 Olschlager F41C 23/02 224/149
5,136,759 A * 8/1992 Armour, II A44B 18/00 24/16 R
5,330,148 A * 7/1994 Floyd B60P 3/075 224/42.4

(Continued)

Primary Examiner — Hilary L Gutman



(74) Attorney, Agent, or Firm — Shannon Warren

(57)

ABSTRACT

A tank tiedown system for securing a tank during transport in a vehicle. The tank tiedown system comprises a perimeter strap assembly, a first hook-and-loop fastener assembly having a first fastener portion and a second fastener portion, a one or more snap hook assemblies, and one or more ring buckles, the one or more ring buckles comprise at least a second ring buckle. The perimeter strap assembly comprises a first end and a second end. The second ring buckle is attached to the second end of the perimeter strap assembly. The first fastener portion and the second fastener portion are attached to the first end of the perimeter strap assembly with the first fastener portion more proximate to the first end than the second fastener portion.

17 Claims, 14 Drawing Sheets



* cited by examiner






FIG. 1






FIG. 3




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 6E




FIG. 6F




FIG. 7A




FIG. 7B




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12A




FIG. 12B




FIG. 13A




FIG. 13B




FIG. 14

1

**PROPANE TANK TIE DOWN SYSTEM AND
METHOD OF USE****CROSS-REFERENCE TO RELATED
APPLICATIONS**

Not applicable.

**STATEMENT REGARDING FEDERALLY
SPONSORED RESEARCH OR DEVELOPMENT
(IF APPLICABLE)**

Not applicable.

**REFERENCE TO SEQUENCE LISTING, A
TABLE, OR A COMPUTER PROGRAM LISTING
COMPACT DISC APPENDIX (IF APPLICABLE)**

Not applicable.

BACKGROUND OF THE INVENTION

Disclosed herein is a tank tiedown system **100** and method of use thereof which can eliminate challenges with securely transporting individual one or more a tank **104**.

Existing methods of transporting one or more said tank **104** either do not securely connect to the transporting vehicle or require separate and generic connection devices not specifically designed for the purpose.

This invention can stay with said tank **104** eliminating the need for separate connection devices or methods.

Said tank tiedown system **100** enables multiple connection options with the transport vehicle eliminating the need for existing inconvenient and time-consuming methods. Said tank tiedown system **100** eliminates loose or unsecured one or more said tank **104**.

This strap-based design with imbedded hooks is installed on said tank **104** to enable easy connection to the transport vehicle's cargo hooks, child car seat connection points or seat-belts.

Said tank tiedown system **100** can comprise an improvement on what currently exists. Previous means of transporting one or more said tank **104** relied on various methods including the use of general purpose bungee straps, cinch straps or ratchet straps. Other methods include wedging said tank **104** which is loose in a vehicle between seats, leveraging a separate heavy item for support or utilizing vehicle seat belts with no connection point to said tank **104**.

One objective of said tank tiedown system **100** is to secure one or more said tank **104** which remain loose or unsecured in a vehicle. The relevant prior art, methods or devices used in connecting the one or more said tank **104** are inconvenient or time consuming.

This invention can stay with said tank **104** eliminating the need for separate connection devices or methods. Said tank tiedown system **100** enables multiple connection options with the transport vehicle eliminating the need for existing inconvenient and time-consuming methods. Said tank tiedown system **100** eliminates loose or unsecured one or more said tank **104**.

Additionally: said tank tiedown system **100** could be used to secure any cylindrical device capable of being transported in a vehicle (i.e. tanks, cans, jugs, bottles, buckets, barrels, etc.).

Relevant prior art known to the Applicant includes: propane tank holders (U.S. Pat. Nos. 5,799,849A, 9,499,105B1, 9,321,404B1, US20140063500A1, and U.S. Pat. No. 6,386,

2

559B1) and for propane tank vehicle anchors (U.S. Pat. Nos. 9,499,105B1, 7,316,435B2, 9,321,404B1, US20140063500A1, and U.S. Pat. No. 6,386,559B1).

BRIEF SUMMARY OF THE INVENTION

a tank tiedown system **100** for securing a tank **104** during transport in a vehicle **118**. Said tank tiedown system **100** comprises a perimeter strap assembly **120**, a first hook-and-loop fastener assembly **208** having a first fastener portion **208a** and a second fastener portion **208b**, a one or more snap hook assemblies **210**, and one or more ring buckles **204**, said one or more ring buckles **204** comprise at least a second ring buckle **204b**. Said perimeter strap assembly **120** comprises a first end **212** and a second end **214**. Said second ring buckle **204b** is attached to said second end **214** of said perimeter strap assembly **120**. Said first fastener portion **208a** and said second fastener portion **208b** are attached to said first end **212** of said perimeter strap assembly **120** with said first fastener portion **208a** more proximate to said first end **212** than said second fastener portion **208b**. Said perimeter strap assembly **120** comprises a strap length **226**. Said strap length **226** is long enough to secure said tank tiedown system **100** around said tank **104** by wrapping said perimeter strap assembly **120** around said tank **104**, doubling a portion of said first end **212** back through a first ring buckle **204a**, and attaching said first fastener portion **208a** to said second fastener portion **208b** of said first hook-and-loop fastener assembly **208**. Said tank tiedown system **100** can comprise a variable diameter **114**, and said tank **104** can comprise a tank diameter **116**. Said tank tiedown system **100** can be configured to adjust said variable diameter **114** to match said variable diameter **114** and securely tighten around said tank **104**. Said one or more snap hook assemblies **210** comprise at least a first snap hook assembly **210a**. Said first snap hook assembly **210a** attach to a portion of said perimeter strap assembly **120** and extends outward from said tank **104** with said tank tiedown system **100** attached around said tank **104**. Said one or more snap hook assemblies **210** are configured to selectively hook and release an anchor point **808** to securely hold said tank **104** with said tank tiedown system **100** within said vehicle **118**.

Said tank tiedown system **100** for securing said tank **104** during transport in said vehicle **118**. Said tank tiedown system **100** comprises said perimeter strap assembly **120**, said first hook-and-loop fastener assembly **208** having said first fastener portion **208a** and said second fastener portion **208b**, said one or more snap hook assemblies **210**, and said one or more ring buckles **204**, said one or more ring buckles **204** comprise at least said second ring buckle **204b**. Said perimeter strap assembly **120** comprises said first end **212** and said second end **214**. Said second ring buckle **204b** is attached to said second end **214** of said perimeter strap assembly **120**. Said first fastener portion **208a** and said second fastener portion **208b** are attached to said first end **212** of said perimeter strap assembly **120** with said first fastener portion **208a** more proximate to said first end **212** than said second fastener portion **208b**. Said perimeter strap assembly **120** comprises said strap length **226**. Said strap length **226** is long enough to secure said tank tiedown system **100** around said tank **104** by wrapping said perimeter strap assembly **120** around said tank **104**, doubling a portion of said first end **212** back through said first ring buckle **204a**, and attaching said first fastener portion **208a** to said second fastener portion **208b** of said first hook-and-loop fastener assembly **208**. Said tank tiedown system **100** can comprise said variable diameter **114**, and said tank **104** can comprise

3

said tank diameter 116. Said tank tiedown system 100 can be configured to adjust said variable diameter 114 to match said variable diameter 114 and securely tighten around said tank 104. Said one or more snap hook assemblies 210 comprise at least said first snap hook assembly 210a. Said first snap hook assembly 210a attach to a portion of said perimeter strap assembly 120 and extends outward from said tank 104 with said tank tiedown system 100 attached around said tank 104. Said one or more snap hook assemblies 210 are configured to selectively hook and release said anchor point 808 to securely hold said tank 104 with said tank tiedown system 100 within said vehicle 118. Said tank tiedown system 100 further comprises a belt loop assembly 122. Said belt loop assembly 122 attaches to a portion of said perimeter strap assembly 120. Said belt loop assembly 122 comprises a belt loop gap 414. Said belt loop gap 414 selectively receives a portion of vehicle seatbelt 1012 prior to buckling said vehicle seatbelt 1012 to securely hold said tank 104 with said tank tiedown system 100 within said vehicle 118 with said vehicle seatbelt 1012 in a buckled configuration 1014.

Said tank tiedown system 100 for securing said tank 104 during transport in said vehicle 118. Said tank tiedown system 100 comprises said perimeter strap assembly 120, said first hook-and-loop fastener assembly 208 having said first fastener portion 208a and said second fastener portion 208b, said one or more snap hook assemblies 210, and said one or more ring buckles 204, said one or more ring buckles 204 comprise at least said second ring buckle 204b. Said perimeter strap assembly 120 comprises said first end 212 and said second end 214. Said second ring buckle 204b is attached to said second end 214 of said perimeter strap assembly 120. Said first fastener portion 208a and said second fastener portion 208b are attached to said first end 212 of said perimeter strap assembly 120 with said first fastener portion 208a more proximate to said first end 212 than said second fastener portion 208b. Said perimeter strap assembly 120 comprises said strap length 226. Said strap length 226 is long enough to secure said tank tiedown system 100 around said tank 104 by wrapping said perimeter strap assembly 120 around said tank 104, doubling a portion of said first end 212 back through said first ring buckle 204a, and attaching said first fastener portion 208a to said second fastener portion 208b of said first hook-and-loop fastener assembly 208. Said tank tiedown system 100 can comprise said variable diameter 114, and said tank 104 can comprise said tank diameter 116. Said tank tiedown system 100 can be configured to adjust said variable diameter 114 to match said variable diameter 114 and securely tighten around said tank 104. Said one or more snap hook assemblies 210 comprise at least said first snap hook assembly 210a. Said first snap hook assembly 210a attach to a portion of said perimeter strap assembly 120 and extends outward from said tank 104 with said tank tiedown system 100 attached around said tank 104. Said one or more snap hook assemblies 210 are configured to selectively hook and release said anchor point 808 to securely hold said tank 104 with said tank tiedown system 100 within said vehicle 118. Said tank tiedown system 100 further comprises said belt loop assembly 122. Said belt loop assembly 122 attaches to a portion of said perimeter strap assembly 120. Said belt loop assembly 122 comprises said belt loop gap 414. Said belt loop gap 414 selectively receives a portion of said vehicle seatbelt 1012 prior to buckling said vehicle seatbelt 1012 to securely hold said tank 104 with said tank tiedown system 100 within said vehicle 118 with said vehicle seatbelt 1012 in said buckled configuration 1014. Said belt loop assembly 122 comprises

4

a strap 314 comprising a first end 316 and a second end 318. attaching said belt loop assembly 122 to said perimeter strap assembly 120 comprises: wrapping said belt loop assembly 122 around a portion of said perimeter strap assembly 120, and sewing said first end 316 and said second end 318 of said strap 314 to a back side of said perimeter strap assembly 120.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

FIG. 1 illustrates a perspective overview of a tank tiedown system 100 and a tank 104, in a detached configuration 102.

FIGS. 2A and 2B illustrate an elevated front and rear view of said tank tiedown system 100.

FIG. 3 illustrates an exploded elevated front view of said tank tiedown system 100.

FIGS. 4A and 4B illustrate a front and rear elevated view of said belt loop assembly 122; respectively.

FIGS. 5A, 5B, and 5C illustrate an elevated overview of said first snap hook assembly 210a in a detached configuration 500a, a second configuration 500b, and an attached configuration 500c.

FIGS. 6A, 6B, 6C, 6D, 6E and 6F illustrate front, rear and side views of said first snap hook assembly 210a and said second snap hook assembly 210b.

FIGS. 7A and 7B illustrate an elevated front and rear view of said tank 104 with said tank tiedown system 100 attached.

FIG. 8 illustrates a perspective overview of said tank tiedown system 100 in a truck bed 802 in a short hook installed configuration 804.

FIG. 9 illustrates an elevated rear view of a long hook installed configuration 904 with said tank tiedown system 100 attached to said child car connection point 902 in said vehicle 118.

FIG. 10 illustrates a perspective overview of said tank tiedown system 100 in an installed seatbelt configuration 1002.

FIG. 11 illustrates a perspective overview of a tank tie down system 1102.

FIGS. 12A and 12B illustrate an elevated front and rear view of said double belt loop assembly 1104.

FIGS. 13A and 13B illustrate an elevated front and rear view of said second strap 202b with said double belt loop assembly 1104 and said loop restraint strap assembly 1106 of said tank tie down system 1102.

FIG. 14 illustrates an elevated front view of said tank tie down system 1102 in said installed seatbelt configuration 1002.

DETAILED DESCRIPTION OF THE INVENTION

The following description is presented to enable any person skilled in the art to make and use the invention as claimed and is provided in the context of the particular examples discussed below, variations of which will be readily apparent to those skilled in the art. In the interest of clarity, not all features of an actual implementation are described in this specification. It will be appreciated that in the development of any such actual implementation (as in any development project), design decisions must be made to achieve the designers' specific goals (e.g., compliance with system- and business-related constraints), and that these goals will vary from one implementation to another. It will also be appreciated that such development effort might be complex and time-consuming, but would nevertheless be a

5

routine undertaking for those of ordinary skill in the field of the appropriate art having the benefit of this disclosure. Accordingly, the claims appended hereto are not intended to be limited by the disclosed embodiments, but are to be accorded their widest scope consistent with the principles and features disclosed herein.

FIG. 1 illustrates a perspective overview of a tank tiedown system **100** and a tank **104**, in a detached configuration **102**.

In one embodiment, said tank tiedown system **100** can be configured to securely hold said tank **104**. In one embodiment, said tank tiedown system **100** can eliminate challenges in securing and/or transporting said tank **104**, as illustrated and discussed below.

In one embodiment, said tank **104** can comprise a propane gas tank.

In one embodiment, said tank tiedown system **100** can attach to and remain attached to said tank **104** for the useful ownership period of said tank **104**; e.g., attach to a new tank at the store, transport it home, extract gas from said tank **104** until empty, return to store, remove said tank tiedown system **100**, exchange old tank for a new tank, attach said tank tiedown system **100** to the new tank.

Said tank tiedown system **100** can attach around a side wall **106** which can comprise an external circumference about a middle portion of said tank **104** between a top end **108** and a bottom end **110**, as illustrated.

One objective of said tank tiedown system **100** can comprise securing said tank **104** in a vehicle **118** during transportation to and from a purchase site. A one or more connectors are provided to securely mount said tank **104** to a portion of a vehicle, as discussed below.

Additionally: said tank tiedown system **100** could be used to secure any cylindrical device capable of being transported in a vehicle (i.e. tanks, cans, jugs, bottles, buckets, barrels, etc.).

In one embodiment, said tank tiedown system **100** can comprise a variable diameter **114**, and said tank **104** can comprise a tank diameter **116**. Said tank tiedown system **100** can be configured to adjust said variable diameter **114** to match said tank diameter **116** and securely tighten around said tank **104**, as discussed herein.

In one embodiment, said tank tiedown system **100** can comprise a perimeter strap assembly **120** and a belt loop assembly **122**.

FIGS. 2A and 2B illustrate an elevated front and rear view of said tank tiedown system **100**.

In one embodiment, said tank tiedown system **100** can comprise, one or more ring buckles **204** (which can comprise a first ring buckle **204a**, a second ring buckle **204b**, and a third ring buckle **204c**), a stitching **206**, a first hook-and-loop fastener assembly **208** (which can comprise a first fastener portion **208a**, and a second fastener portion **208b**), a one or more snap hook assemblies **210** (which can comprise a first snap hook assembly **210a**, and a second snap hook assembly **210b**), and a strap magnet **218**.

Said perimeter strap assembly **120** can be created from a two or more straps **202** (which can comprise a first strap **202a**, a second strap **202b**, and a third strap **202c**) attached to one another with said one or more ring buckles **204** and said stitching **206**. Said perimeter strap assembly **120** can comprise a first end **212** and a second end **214**. Said third strap **202c**, said second strap **202b**, and/or said first strap **202a** adjustably attached to one another to create a single adjustable strap.

In one embodiment, said strap magnet **218** can hold a portion of said belt loop assembly **122** against a metal body

6

such as said tank **104** to further ensure safety of said tank **104**, and said tank tiedown system **100**.

Said perimeter strap assembly **120** can comprise a strap length **226**; wherein, said strap length **226** can be long enough to wrap around said tank **104**, and double back to attach said first hook-and-loop fastener assembly **208** to one another.

FIG. 3 illustrates an exploded elevated front view of said tank tiedown system **100**.

Said first strap **202a** comprises a first end **302** and a second end **304**; said second strap **202b** comprises a first end **306** and a second end **308**; and said third strap **202c** comprises a first end **310** and a second end **312**.

In one embodiment, attaching said two or more straps **202** to one another can comprise a sewn in process comprising looping one end of a strap through one among said one or more ring buckles **204**, pulling a portion of said strap back through and sewing it back onto itself with said stitching **206**. This sewn in process can be repeated with: said first end **306** and said second end **304** attached to said third ring buckle **204c**; said first end **310** and said second end **308** attached to said first ring buckle **204a**; and said second end **312** attached to said second ring buckle **204b**.

In one embodiment, said first strap **202a** is not sewn to said second ring buckle **204b**, but can be selectively attached and detached using said first fastener portion **208a** and said second fastener portion **208b** by: attaching said first fastener portion **208a** and said second fastener portion **208b** to said first strap **202a** with said first fastener portion **208a** closer to said first end **302** of said first strap **202a** than said second fastener portion **208b**, feeding a portion of said first fastener portion **208a** through said second ring buckle **204b**, pulling a portion of said first fastener portion **208a** back over a portion of said second fastener portion **208b**, and pressing said first hook-and-loop fastener assembly **208** together.

In one embodiment, said one or more snap hook assemblies **210** can attach to a portion of said one or more ring buckles **204**. For example, in one embodiment, said first snap hook assembly **210a** can connect to said third ring buckle **204c**, and said second snap hook assembly **210b** can connect to said first ring buckle **204a**.

In one embodiment, said stitching **206** can comprise a heavy duty thread of sufficient strength to secure said two or more straps **202** to one another and/or said first hook-and-loop fastener assembly **208**.

In one embodiment, said belt loop assembly **122** can comprise a strap **314** comprising a first end **316** and a second end **318**. Said belt loop assembly **122** can be wrapped around a portion of said perimeter strap assembly **120** (such as around said second strap **202b**), with its ends sewn to a back side (that is interior portion) of said perimeter strap assembly **120**. In one embodiment, each end of said strap **314** is pulled back around and sewn to itself using said stitching **206**, as illustrated.

FIGS. 4A and 4B illustrate a front and rear elevated view of said belt loop assembly **122**; respectively.

Said belt loop assembly **122** can be looped over a center section **412** of said second strap **202b** between said first ring buckle **204a** and said third ring buckle **204c** with said strap **314**.

FIGS. 5A, 5B, and 5C illustrate an elevated overview of said first snap hook assembly **210a** in a detached configuration **500a**, a second configuration **500b**, and an attached configuration **500c**.

Said one or more ring buckles **204** can each comprise an eye **502** comprising an aperture within a ring rim **504**.

In one embodiment, said one or more snap hook assemblies **210** can each comprise a strap aperture **506**, a snap hook strap **508**, and a snap hook **510**. Said snap hook strap **508** comprises a first end **512** and a second end **514**. Said strap aperture **506** comprise an eye **516** and a ring rim **518**.

Attaching said one or more snap hook assemblies **210** to said one or more ring buckles **204** can comprise: sliding a portion of said snap hook strap **508** through said ring rim **518**, pressing said first end **512** and said second end **514** of said snap hook strap **508** together (said detached configuration **500a**) and sliding the ends through said eye **502** of said one or more ring buckles **204** (said second configuration **500b**), and attaching each of said first end **512** and said second end **514** of said snap hook strap **508** to portions of said two or more straps **202** (said attached configuration **500c**), as illustrated.

In one embodiment, said snap hook strap **508** can be sufficiently long to reach common anchor points, as discussed herein.

In one embodiment, said snap hook **510** can comprise strap metal claw snap hooks.

FIGS. 6A, 6B, 6C, 6D, 6E and 6F illustrate front, rear and side views of said first snap hook assembly **210a** and said second snap hook assembly **210b**.

In one embodiment, said second snap hook assembly **210b**, and said first snap hook assembly **210a** can each comprise a hook catch gap **600** being dissimilar to one another. Said first snap hook assembly **210a** can comprise a first hook catch gap depth **602**, and said second snap hook assembly **210b** can comprise a second hook catch gap depth **604**. In one embodiment, said second hook catch gap depth **604** can be larger than said first hook catch gap depth **602**. For example, in one embodiment, said first hook catch gap depth **602** can comprise $\frac{3}{32}$ " and said second hook catch gap depth **604** can comprise $\frac{1}{2}$ ".

Said first snap hook assembly **210a** can comprise a first snap hook strap **606**, and said second snap hook assembly **210b** can comprise a second snap hook strap **608**. In one embodiment, said first snap hook strap **606** can be longer than said second snap hook strap **608** and therefore said first snap hook assembly **210a** can extend out further from said perimeter strap assembly **120** when assembled.

Each of said one or more snap hook assemblies **210** can comprise a hook portion **610**, a clipping portion **612**, and a hook width **614**. Said hook width **614** can be the same for both said second snap hook assembly **210b**, and said first snap hook assembly **210a**.

FIGS. 7A and 7B illustrate an elevated front and rear view of said tank **104** with said tank tiedown system **100** attached.

As illustrated, said strap magnet **218** can be used to secure a portion of said perimeter strap assembly **120** to said tank **104**.

FIG. 8 illustrates a perspective overview of said tank tiedown system **100** in a truck bed **802** in a short hook installed configuration **804**.

With said tank tiedown system **100** installed on said tank **104**, said tank **104** can be hooked to a utility hook **806** or a child car connection point **902** (illustrated below) in said vehicle **118** for safe and convenient transport. Collectively said utility hook **806** or said child car connection point **902** can be referred to as an anchor point **808**.

As illustrated, said first snap hook strap **606** is only long enough to attach to said perimeter strap assembly **120**, extend through said third ring buckle **204c**, and connect to said first snap hook assembly **210a** without slack in said first snap hook strap **606**. Accordingly, with said tank tiedown system **100** attached to said utility hook **806** with said first

snap hook assembly **210a**, said tank **104** does not have enough slack to bounce around.

In one embodiment, with one or more of said one or more snap hook assemblies **210** under a load or pressure, said perimeter strap assembly **120** can tighten around said tank **104**.

In one embodiment, said tank tiedown system **100** can be installed on said side wall **106** at a height preferred by the end user. For example, said truck bed **802** and said utility hook **806** can require said tank tiedown system **100** relatively high on the cylindrical wall of said tank **104** to limit stretching to reach said utility hook **806**. This functionality could be considered optional.

In one embodiment, a portion of said two or more straps **202** and/or said snap hook strap **508** can comprise rubber straps, so as to ensure said tank **104** is held tight to said vehicle **118** during transportation. This material change could improve durability and/or reduce costs.

In another embodiment, said two or more straps **202** and/or said snap hook strap **508** can comprise synthetic webbing, such as nylon, as is known in the art.

FIG. 9 illustrates an elevated rear view of a long hook installed configuration **904** with said tank tiedown system **100** attached to said child car connection point **902** in said vehicle **118**.

Using a similar procedure as discussed for said truck bed **802**, said utility hook **806** can be used to secure said tank **104** with said tank tiedown system **100**, as illustrated.

In one embodiment, both said second snap hook assembly **210b**, and said first snap hook assembly **210a** can be attached to one or more of said child car connection point **902**. As illustrated here, said second snap hook assembly **210b** is provided with said second snap hook strap **608** which is longer than said first snap hook strap **606**, and therefore is able to rotate 90 degrees to hook to said child car connection point **902**. In another embodiment, said first snap hook assembly **210a** can be used where slack is not desired between said tank **104** and said child car connection point **902**.

In one embodiment, said first hook catch gap depth **602** is wider to accommodate typical mounting points in trucks (such as said utility hook **806**) and said second hook catch gap depth **604** can be more narrow to accommodate typical mounting points inside of vehicle cabins (such as said child car connection point **902**).

FIG. 10 illustrates a perspective overview of said tank tiedown system **100** in an installed seatbelt configuration **1002**.

If an adequate anchor such as said utility hook **806** and/or said child car connection point **902** are not available, said tank **104** can be secured in a vehicle seat **906** by: placing said vehicle seatbelt **1012** between said belt loop assembly **122** and said perimeter strap assembly **120**, securing with said belt loop assembly **122**, and attaching said vehicle seatbelt **1012** to a seatbelt receiver **1008**. In one embodiment, said tank tiedown system **100** can be positioned above a center of gravity on said side wall **106** to align said tank tiedown system **100** with a lower seatbelt portion **1010**.

Each of the three transport vehicle connection methods are used independently and, as such, the two methods not in use could be considered optional. Further, each of the three transport vehicle connection methods (snap hook one, snap hook two and seatbelt strap) can be configured in any order along the length of said tank tiedown system **100** as part of the overall solution.

FIG. 11 illustrates a perspective overview of a tank tie down system **1102**.

As illustrated, said tank tie down system **1102** and said tank tiedown system **100** can be similar in construction but for a few features. Namely, a double belt loop assembly **1104** rather than said belt loop assembly **122**, and a loop restraint strap assembly **1106**.

FIGS. **12A** and **12B** illustrate an elevated front and rear view of said double belt loop assembly **1104**.

In one embodiment, said double belt loop assembly **1104** can comprise a loop assembly strap **1200** configured with a first loop **1202**, a second loop **1204**, a first stitches **1206** at a first end **1208**, and a second stitches **1210** at a second end **1212**.

FIGS. **13A** and **13B** illustrate an elevated front and rear view of said second strap **202b** with said double belt loop assembly **1104** and said loop restraint strap assembly **1106** of said tank tie down system **1102**.

In one embodiment, said tank tie down system **1102** can comprise said second strap **202b** with said double belt loop assembly **1104** and said loop restraint strap assembly **1106**, as illustrated.

In one embodiment, said loop restraint strap assembly **1106** can comprise a restraint strap **1300** having a first end **1302** and a second end **1304**, a second hook-and-loop fasteners **1306** (which can comprise a first portion **1306a**, and a second portion **1306b**), and a second end stitching **1308**. Said second end stitching **1308** can attach said second end **1304** to a portion of said perimeter strap assembly **120**. Said first end **1302** can comprise said second portion **1306b** which can align with said first portion **1306a** which is attached to a portion of said perimeter strap assembly **120**.

Said double belt loop assembly **1104** can attach to said second strap **202b** by: opening said loop restraint strap assembly **1106** (an open restraint configuration **1322a**), sliding a portion of said second strap **202b** through said first loop **1202** (a first loop configuration **1320a**), sliding a portion of said loop restraint strap assembly **1106** through said second loop **1204** of said double belt loop assembly **1104** (a second loop configuration **1320b**), and attaching said second portion **1306b** of said loop restraint strap assembly **1106** to said first portion **1306a** of said second strap **202b** (a second restraint configuration **1322b**).

In one embodiment, with said loop restraint strap assembly **1106** in said second restraint configuration **1322b** there is a restraint gap **1324** formed between said second strap **202b** and said restraint strap **1300**. Likewise, with said double belt loop assembly **1104** in said second loop configuration **1320b**, a belt loop gap **414** can be formed between said first end **1208** and said second end **1212** of said loop assembly strap **1200**, as illustrated.

FIG. **14** illustrates an elevated front view of said tank tie down system **1102** in said installed seatbelt configuration **1002**.

As illustrated, said tank tiedown system **100** and said tank tie down system **1102** can function in a similar manner viz a viz said installed seatbelt configuration **1002**.

The following sentences are included with reference to the claims.

Said tank tiedown system **100** for securing said tank **104** during transport in said vehicle **118**. Said tank tiedown system **100** comprises said perimeter strap assembly **120**, said first hook-and-loop fastener assembly **208** having said first fastener portion **208a** and said second fastener portion **208b**, said one or more snap hook assemblies **210**, and said one or more ring buckles **204**, said one or more ring buckles **204** comprise at least said second ring buckle **204b**. Said perimeter strap assembly **120** comprises said first end **212** and said second end **214**. Said second ring buckle **204b** can

be attached to said second end **214** of said perimeter strap assembly **120**. Said first fastener portion **208a** and said second fastener portion **208b** can be attached to said first end **212** of said perimeter strap assembly **120** with said first fastener portion **208a** more proximate to said first end **212** than said second fastener portion **208b**. Said perimeter strap assembly **120** comprises said strap length **226**. Said strap length **226** can be long enough to secure said tank tiedown system **100** around said tank **104** by wrapping said perimeter strap assembly **120** around said tank **104**, doubling a portion of said first end **212** back through said first ring buckle **204a**, and attaching said first fastener portion **208a** to said second fastener portion **208b** of said first hook-and-loop fastener assembly **208**. Said tank tiedown system **100** can comprise said variable diameter **114**, and said tank **104** can comprise said tank diameter **116**. Said tank tiedown system **100** can be configured to adjust said variable diameter **114** to match said variable diameter **114** and securely tighten around said tank **104**. Said one or more snap hook assemblies **210** comprise at least said first snap hook assembly **210a**. Said first snap hook assembly **210a** attach to a portion of said perimeter strap assembly **120** and extends outward from said tank **104** with said tank tiedown system **100** attached around said tank **104**. Said one or more snap hook assemblies **210** can be configured to selectively hook and release said anchor point **808** to securely hold said tank **104** with said tank tiedown system **100** within said vehicle **118**.

Said perimeter strap assembly **120** can be created from said two or more straps **202**. Said tank tiedown system **100** further comprises said one or more ring buckles **204** comprising at least said second ring buckle **204b** and said first ring buckle **204a**. Said two or more straps **202** attached to one another with said one or more ring buckles **204** and said stitching **206** to create a single adjustable strap. Said two or more straps **202** comprise at least said first strap **202a** having said first end **302** and said second end **304**, and said second strap **202b** having said first end **306** and said second end **308**. Said two or more straps **202** to one another comprises a sewn in process comprising looping one end of a strap through one among said one or more ring buckles **204**, pulling a portion of said strap back through and sewing it back onto itself with said stitching **206**. Said first strap **202a** attaches to said second strap **202b** by applying said sewn in process with: said second end **304** of said first strap **202a** to said second ring buckle **204b**, and said first end **306** of said second strap **202b** to said second ring buckle **204b**. Said one or more ring buckles **204** each comprise said eye **502** comprising an aperture within said ring rim **504**. Said one or more snap hook assemblies **210** each comprise said strap aperture **506**, said snap hook strap **508**, and said snap hook **510**. Said snap hook strap **508** comprises said first end **512** and said second end **514**. Said strap aperture **506** comprise said eye **516** and said ring rim **518**. Attaching said one or more snap hook assemblies **210** to said one or more ring buckles **204** comprises: sliding a portion of said snap hook strap **508** through said ring rim **518**, pressing said first end **512** and said second end **514** of said snap hook strap **508** together, sliding the ends through said eye **502** of said one or more ring buckles **204**, and attaching each of said first end **512** and said second end **514** of said snap hook strap **508** to portions of said two or more straps **202**. Said first snap hook assembly **210a** attaches to and extends from said second ring buckle **204b**.

Said tank tiedown system **100** further comprises said stitching **206** said stitching **206** comprises a heavy duty

11

thread of sufficient strength to secure said two or more straps **202** to one another and said first hook-and-loop fastener assembly **208**.

Said one or more snap hook assemblies **210** further comprise said second snap hook assembly **210b**. Said two or more straps **202** further comprise said third strap **202c**. Said one or more ring buckles **204** further comprise said third ring buckle **204c**. Said second strap **202b** and said third strap **202c** attach to one another with said third ring buckle **204c** in the same manner as said first strap **202a** and said second strap **202b** attach to one another using said first ring buckle **204a**. Said second snap hook assembly **210b** attaches to said third ring buckle **204c**.

Said first snap hook assembly **210a** and said second snap hook assembly **210b** each comprise said hook catch gap **600** and said snap hook strap **508** being dissimilar to one another. Said first snap hook assembly **210a** comprises said first hook catch gap depth **602** and said first snap hook strap **606**. Said second snap hook assembly **210b** comprises said second hook catch gap depth **604** and said second snap hook strap **608**. Said second hook catch gap depth **604** can be larger than said first hook catch gap depth **602**. Said first snap hook strap **606** can be longer than said second snap hook strap **608** and therefore said first snap hook assembly **210a** extends out further from said perimeter strap assembly **120** when said one or more snap hook assemblies **210** can be assembled with said perimeter strap assembly **120**.

Said first hook catch gap depth **602** comprises $\frac{3}{32}$ " inch and said second hook catch gap depth **604** comprises $\frac{1}{2}$ " inch.

Said first hook catch gap depth **602** can be wider to accommodate said anchor point **808** in trucks such as said utility hook **806**, said second hook catch gap depth **604** can be narrower to accommodate said anchor point **808** inside of vehicle cabins such as said child car connection point **902**, and said second snap hook strap **608** can be longer than said first snap hook strap **606** and can be therefore able to rotate 90 degrees to hook to said child car connection point **902**.

Said tank tiedown system **100** further comprises said belt loop assembly **122**. Said belt loop assembly **122** attaches to a portion of said perimeter strap assembly **120**. Said belt loop assembly **122** comprises said belt loop gap **414**. Said belt loop gap **414** selectively receives a portion of said vehicle seatbelt **1012** prior to buckling said vehicle seatbelt **1012** to securely hold said tank **104** with said tank tiedown system **100** within said vehicle **118** with said vehicle seatbelt **1012** in a buckled configuration **1014**.

Said belt loop assembly **122** comprises said strap **314** comprising said first end **316** and said second end **318**. attaching said belt loop assembly **122** to said perimeter strap assembly **120** comprises: wrapping said belt loop assembly **122** around a portion of said perimeter strap assembly **120**, and sewing said first end **316** and said second end **318** of said strap **314** to a back side of said perimeter strap assembly **120**.

Said tank tiedown system **100** further comprises said strap magnet **218**. Said strap magnet **218** can be attached to said belt loop assembly **122**. Said strap magnet **218** holds a portion of said belt loop assembly **122** against a metal body such as said tank **104** to further ensure safety of said tank **104** and said tank tiedown system **100**.

Said tank tiedown system **100** attaches to and remain attached to said tank **104** for the useful ownership period of said tank **104**.

Said tank tiedown system **100** for securing said tank **104** during transport in said vehicle **118**. Said tank tiedown system **100** comprises said perimeter strap assembly **120**,

12

said first hook-and-loop fastener assembly **208** having said first fastener portion **208a** and said second fastener portion **208b**, said one or more snap hook assemblies **210**, and said one or more ring buckles **204**, said one or more ring buckles **204** comprise at least said second ring buckle **204b**. Said perimeter strap assembly **120** comprises said first end **212** and said second end **214**. Said second ring buckle **204b** can be attached to said second end **214** of said perimeter strap assembly **120**. Said first fastener portion **208a** and said second fastener portion **208b** can be attached to said first end **212** of said perimeter strap assembly **120** with said first fastener portion **208a** more proximate to said first end **212** than said second fastener portion **208b**. Said perimeter strap assembly **120** comprises said strap length **226**. Said strap length **226** can be long enough to secure said tank tiedown system **100** around said tank **104** by wrapping said perimeter strap assembly **120** around said tank **104**, doubling a portion of said first end **212** back through said first ring buckle **204a**, and attaching said first fastener portion **208a** to said second fastener portion **208b** of said first hook-and-loop fastener assembly **208**. Said tank tiedown system **100** can comprise said variable diameter **114**, and said tank **104** can comprise said tank diameter **116**. Said tank tiedown system **100** can be configured to adjust said variable diameter **114** to match said variable diameter **114** and securely tighten around said tank **104**. Said one or more snap hook assemblies **210** comprise at least said first snap hook assembly **210a**. Said first snap hook assembly **210a** attach to a portion of said perimeter strap assembly **120** and extends outward from said tank **104** with said tank tiedown system **100** attached around said tank **104**. Said one or more snap hook assemblies **210** can be configured to selectively hook and release said anchor point **808** to securely hold said tank **104** with said tank tiedown system **100** within said vehicle **118**. Said tank tiedown system **100** further comprises said belt loop assembly **122**. Said belt loop assembly **122** attaches to a portion of said perimeter strap assembly **120**. Said belt loop assembly **122** comprises said belt loop gap **414**. Said belt loop gap **414** selectively receives a portion of said vehicle seatbelt **1012** prior to buckling said vehicle seatbelt **1012** to securely hold said tank **104** with said tank tiedown system **100** within said vehicle **118** with said vehicle seatbelt **1012** in said buckled configuration **1014**.

Said belt loop assembly **122** comprises said strap **314** comprising said first end **316** and said second end **318**. attaching said belt loop assembly **122** to said perimeter strap assembly **120** comprises: wrapping said belt loop assembly **122** around a portion of said perimeter strap assembly **120**, and sewing said first end **316** and said second end **318** of said strap **314** to a back side of said perimeter strap assembly **120**.

Said perimeter strap assembly **120** can be created from said two or more straps **202**. Said tank tiedown system **100** further comprises said one or more ring buckles **204** comprising at least said second ring buckle **204b** and said first ring buckle **204a**. Said two or more straps **202** attached to one another with said one or more ring buckles **204** and said stitching **206** to create a single adjustable strap. Said two or more straps **202** comprise at least said first strap **202a** having said first end **302** and said second end **304**, and said second strap **202b** having said first end **306** and said second end **308**. attaching said two or more straps **202** to one another comprises a sewn in process comprising looping one end of a strap through one among said one or more ring buckles **204**, pulling a portion of said strap back through and sewing it back onto itself with said stitching **206**. Said first strap **202a** attaches to said second strap **202b** by applying said

13

sewn in process with: said second end **304** of said first strap **202a** to said second ring buckle **204b**, and said first end **306** of said second strap **202b** to said second ring buckle **204b**. Said one or more ring buckles **204** each comprise said eye **502** comprising an aperture within said ring rim **504**. Said one or more snap hook assemblies **210** each comprise said strap aperture **506**, said snap hook strap **508**, and said snap hook **510**. Said snap hook strap **508** comprises said first end **512** and said second end **514**. Said strap aperture **506** comprise said eye **516** and said ring rim **518**. Attaching said one or more snap hook assemblies **210** to said one or more ring buckles **204** comprises: sliding a portion of said snap hook strap **508** through said ring rim **518**, pressing said first end **512** and said second end **514** of said snap hook strap **508** together, sliding the ends through said eye **502** of said one or more ring buckles **204**, and attaching each of said first end **512** and said second end **514** of said snap hook strap **508** to portions of said two or more straps **202**. Said first snap hook assembly **210a** attaches to and extends from said second ring buckle **204b**.

Said one or more snap hook assemblies **210** further comprise said second snap hook assembly **210b**. Said two or more straps **202** further comprise said third strap **202c**. Said one or more ring buckles **204** further comprise said third ring buckle **204c**. Said second strap **202b** and said third strap **202c** attach to one another with said third ring buckle **204c** in the same manner as said first strap **202a** and said second strap **202b** attach to one another using said first ring buckle **204a**. Said second snap hook assembly **210b** attaches to said third ring buckle **204c**.

Said tank tiedown system **100** for securing said tank **104** during transport in said vehicle **118**. Said tank tiedown system **100** comprises said perimeter strap assembly **120**, said first hook-and-loop fastener assembly **208** having said first fastener portion **208a** and said second fastener portion **208b**, said one or more snap hook assemblies **210**, and said one or more ring buckles **204**, said one or more ring buckles **204** comprise at least said second ring buckle **204b**. Said perimeter strap assembly **120** comprises said first end **212** and said second end **214**. Said second ring buckle **204b** can be attached to said second end **214** of said perimeter strap assembly **120**. Said first fastener portion **208a** and said second fastener portion **208b** can be attached to said first end **212** of said perimeter strap assembly **120** with said first fastener portion **208a** more proximate to said first end **212** than said second fastener portion **208b**. Said perimeter strap assembly **120** comprises said strap length **226**. Said strap length **226** can be long enough to secure said tank tiedown system **100** around said tank **104** by wrapping said perimeter strap assembly **120** around said tank **104**, doubling a portion of said first end **212** back through said first ring buckle **204a**, and attaching said first fastener portion **208a** to said second fastener portion **208b** of said first hook-and-loop fastener assembly **208**. Said tank tiedown system **100** can comprise said variable diameter **114**, and said tank **104** can comprise said tank diameter **116**. Said tank tiedown system **100** can be configured to adjust said variable diameter **114** to match said variable diameter **114** and securely tighten around said tank **104**. Said one or more snap hook assemblies **210** comprise at least said first snap hook assembly **210a**. Said first snap hook assembly **210a** attach to a portion of said perimeter strap assembly **120** and extends outward from said tank **104** with said tank tiedown system **100** attached around said tank **104**. Said one or more snap hook assemblies **210** can be configured to selectively hook and release said anchor point **808** to securely hold said tank **104** with said tank tiedown system **100** within said vehicle **118**. Said tank tiedown

14

system **100** further comprises said belt loop assembly **122**. Said belt loop assembly **122** attaches to a portion of said perimeter strap assembly **120**. Said belt loop assembly **122** comprises said belt loop gap **414**. Said belt loop gap **414** selectively receives a portion of said vehicle seatbelt **1012** prior to buckling said vehicle seatbelt **1012** to securely hold said tank **104** with said tank tiedown system **100** within said vehicle **118** with said vehicle seatbelt **1012** in said buckled configuration **1014**. Said belt loop assembly **122** comprises said strap **314** comprising said first end **316** and said second end **318**. attaching said belt loop assembly **122** to said perimeter strap assembly **120** comprises: wrapping said belt loop assembly **122** around a portion of said perimeter strap assembly **120**, and sewing said first end **316** and said second end **318** of said strap **314** to a back side of said perimeter strap assembly **120**.

Said tank tiedown system **100** further comprises said strap magnet **218**. Said strap magnet **218** can be attached to said belt loop assembly **122**. Said strap magnet **218** holds a portion of said belt loop assembly **122** against a metal body such as said tank **104** to further ensure safety of said tank **104** and said tank tiedown system **100**.

Various changes in the details of the illustrated operational methods are possible without departing from the scope of the following claims. Some embodiments may combine the activities described herein as being separate steps. Similarly, one or more of the described steps may be omitted, depending upon the specific operational environment the method is being implemented in. It is to be understood that the above description is intended to be illustrative, and not restrictive. For example, the above-described embodiments may be used in combination with each other. Many other embodiments will be apparent to those of skill in the art upon reviewing the above description. The scope of **100** should, therefore, be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled. In the appended claims, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein.”

The invention claimed is:

1. A tank tiedown system for securing a tank during transport in a vehicle, wherein:

said tank tiedown system comprises a perimeter strap assembly, a first hook-and-loop fastener assembly having a first fastener portion and a second fastener portion, a one or more snap hook assemblies, and one or more ring buckles,

said one or more ring buckles comprise at least a first ring buckle;

said perimeter strap assembly comprises a first end and a second end;

said first ring buckle is attached to said second end of said perimeter strap assembly;

said first fastener portion and said second fastener portion are attached to said first end of said perimeter strap assembly with said first fastener portion more proximate to said first end than said second fastener portion;

said perimeter strap assembly comprises a strap length;

said strap length is long enough to secure said tank tiedown system around said tank by wrapping said perimeter strap assembly around said tank, doubling a portion of said first end back through said first ring buckle, and

15

attaching said first fastener portion to said second fastener portion of said first hook-and-loop fastener assembly;

said tank tiedown system can comprise a variable diameter, and said tank can comprise a tank diameter;

said tank tiedown system can be configured to adjust said variable diameter to match said tank diameter and securely tighten around said tank;

said one or more snap hook assemblies comprise at least a first snap hook assembly;

said first snap hook assembly attaches to a portion of said perimeter strap assembly and extends outward from said tank with said tank tiedown system attached around said tank;

said one or more snap hook assemblies are configured to selectively hook and release an anchor point to securely hold said tank with said tank tiedown system within said vehicle;

each among said one or more snap hook assemblies comprise a hook catch gap, a hook portion, and a clipping portion;

said hook portion and said clipping portion comprise a loop around said hook catch gap; and

said clipping portion is configured to selectively open and close to allow said one or more snap hook assemblies to snap around said anchor point and securely hold said tank to said anchor point.

2. The tank tiedown system of claim 1, wherein:

said perimeter strap assembly is created from a two or more straps;

said tank tiedown system further comprises said one or more ring buckles comprising at least said second ring buckle and said first ring buckle;

said two or more straps attached to one another with said one or more ring buckles and a stitching to create a single adjustable strap;

said two or more straps comprise at least a first strap having a first end and a second end, and a second strap having a first end and a second end;

attaching said two or more straps to one another comprises a sewn in process comprising looping one end of a strap through one among said one or more ring buckles,

pulling a portion of said strap back through and sewing it back onto itself with said stitching;

said first strap attaches to said second strap by applying said sewn in process with:

said second end of said first strap to said second ring buckle, and

said first end of said second strap to said second ring buckle;

said one or more ring buckles each comprise an eye comprising an aperture within a ring rim;

said one or more snap hook assemblies each comprise a strap aperture, a snap hook strap, and a snap hook;

said snap hook strap comprises a first end and a second end;

said strap aperture comprise an eye and a ring rim;

attaching said one or more snap hook assemblies to said one or more ring buckles comprises:

sliding a portion of said snap hook strap through said ring rim,

pressing said first end and said second end of said snap hook strap together,

sliding said first end and said second end through said eye of said one or more ring buckles, and

16

attaching said first end of said snap hook strap to one among said two or more straps and said second end of said snap hook strap to a different one among of said two or more straps; and

said first snap hook assembly attaches to and extends from said second ring buckle.

3. The tank tiedown system of claim 2, wherein:

said tank tiedown system further comprises said stitching; and

said stitching is configured to secure said two or more straps to one another and said first hook-and-loop fastener assembly.

4. The tank tiedown system of claim 2, wherein:

said one or more snap hook assemblies further comprise a second snap hook assembly;

said two or more straps further comprise a third strap;

said one or more ring buckles further comprise a third ring buckle;

said second strap and said third strap attach to one another with said third ring buckle in the same manner as said first strap and said second strap attach to one another using said first ring buckle; and

said second snap hook assembly attaches to said third ring buckle.

5. The tank tiedown system of claim 4, wherein:

said first snap hook assembly and said second snap hook assembly each comprise said hook catch gap and said snap hook strap being dissimilar to one another;

said first snap hook assembly comprises a first hook catch gap depth and a first snap hook strap;

said second snap hook assembly comprises a second hook catch gap depth and a second snap hook strap;

said second hook catch gap depth is larger than said first hook catch gap depth; and

said first snap hook strap is longer than said second snap hook strap and therefore said first snap hook assembly extends out further from said perimeter strap assembly when said one or more snap hook assemblies are assembled with said perimeter strap assembly.

6. The tank tiedown system of claim 5, wherein:

said first hook catch gap depth comprises $\frac{3}{32}$ " inch and said second hook catch gap depth comprises $\frac{1}{2}$ " inch.

7. The tank tiedown system of claim 6, wherein:

said first hook catch gap depth is wider to accommodate said anchor point in trucks such as a utility hook,

said second hook catch gap depth is narrower to accommodate said anchor point inside of vehicle cabins such as a child car connection point, and

said second snap hook strap is longer than said first snap hook strap and is therefore able to rotate 90 degrees to hook to said child car connection point.

8. The tank tiedown system of claim 1, wherein:

said tank tiedown system further comprises a belt loop assembly;

said belt loop assembly attaches to a portion of said perimeter strap assembly;

said belt loop assembly comprises a belt loop gap; and

said belt loop gap selectively receives a portion of vehicle seatbelt prior to buckling said vehicle seatbelt to securely hold said tank with said tank tiedown system within said vehicle with said vehicle seatbelt in a buckled configuration.

9. The tank tiedown system of claim 8, wherein:

said belt loop assembly comprises a strap comprising a first end and a second end;

attaching said belt loop assembly to said perimeter strap assembly comprises:

17

wrapping said belt loop assembly around a portion of said perimeter strap assembly, and
sewing said first end and said second end of said strap to a back side of said perimeter strap assembly.

10. The tank tiedown system of claim 9, wherein:

said tank tiedown system further comprises a strap magnet;

said strap magnet is attached to said belt loop assembly; and

said strap magnet holds a portion of said belt loop assembly against a metal body such as said tank.

11. The tank tiedown system of claim 1, wherein,

said tank tiedown system attaches to and remains attached to said tank for the useful ownership period of said tank.

12. A tank tiedown system for securing a tank during transport in a vehicle, wherein:

said tank tiedown system comprises a perimeter strap assembly, a first hook-and-loop fastener assembly having a first fastener portion and a second fastener portion, a one or more snap hook assemblies, and one or more ring buckles,

said one or more ring buckles comprise at least a first ring buckle;

said perimeter strap assembly comprises a first end and a second end;

said first ring buckle is attached to said second end of said perimeter strap assembly;

said first fastener portion and said second fastener portion are attached to said first end of said perimeter strap assembly with said first fastener portion more proximate to said first end than said second fastener portion; said perimeter strap assembly comprises a strap length; said strap length is long enough to secure said tank tiedown system around said tank by

wrapping said perimeter strap assembly around said tank,

doubling a portion of said first end back through said second ring buckle, and

attaching said first fastener portion to said second fastener portion of said first hook-and-loop fastener assembly;

said tank tiedown system can comprise a variable diameter, and said tank can comprise a tank diameter;

said tank tiedown system can be configured to adjust said variable diameter to match said tank diameter and securely tighten around said tank;

said one or more snap hook assemblies comprise at least a first snap hook assembly;

said first snap hook assembly attaches to a portion of said perimeter strap assembly and extends outward from said tank with said tank tiedown system attached around said tank;

said one or more snap hook assemblies are configured to selectively hook and release an anchor point to securely hold said tank with said tank tiedown system within said vehicle;

said tank tiedown system further comprises a belt loop assembly;

said belt loop assembly attaches to a portion of said perimeter strap assembly;

said belt loop assembly comprises a belt loop gap; and said belt loop gap selectively receives a portion of vehicle seatbelt prior to buckling said vehicle seatbelt to securely hold said tank with said tank tiedown system within said vehicle with said vehicle seatbelt in a buckled configuration.

18

13. The tank tiedown system of claim 12, wherein:

said belt loop assembly comprises a strap comprising a first end and a second end;

attaching said belt loop assembly to said perimeter strap assembly comprises:

wrapping said belt loop assembly around a portion of said perimeter strap assembly, and

sewing said first end and said second end of said strap to a back side of said perimeter strap assembly.

14. The tank tiedown system of claim 13, wherein:

said tank tiedown system further comprises a strap magnet;

said strap magnet is attached to said belt loop assembly; and

said strap magnet holds a portion of said belt loop assembly against a metal body such as said tank.

15. The tank tiedown system of claim 14, wherein:

said perimeter strap assembly is created from a two or more straps;

said tank tiedown system further comprises said one or more ring buckles comprising at least a second ring buckle and said first ring buckle;

said two or more straps attached to one another with said one or more ring buckles and a stitching to create a single adjustable strap;

said two or more straps comprise at least

a first strap having a first end and a second end, and a second strap having a first end and a second end;

attaching said two or more straps to one another comprises a sewn in process comprising looping one end of a strap through one among said one or more ring buckles,

pulling a portion of said strap back through and sewing it back onto itself with said stitching;

said first strap attaches to said second strap by applying said sewn in process with:

said second end of said first strap to said second ring buckle, and

said first end of said second strap to said second ring buckle;

said one or more ring buckles each comprise an eye comprising an aperture within a ring rim;

said one or more snap hook assemblies each comprise a strap aperture, a snap hook strap, and a snap hook;

said snap hook strap comprises a first end and a second end;

said strap aperture comprise an eye and a ring rim;

attaching said one or more snap hook assemblies to said one or more ring buckles comprises:

sliding a portion of said snap hook strap through said ring rim,

pressing said first end and said second end of said snap hook strap together,

sliding the ends through said eye of said one or more ring buckles, and

attaching said first end of said snap hook strap to one among said two or more straps and said second end of said snap hook strap to a different one among of said two or more straps; and

said first snap hook assembly attaches to and extends from said second ring buckle.

16. The tank tiedown system of claim 15, wherein:

said one or more snap hook assemblies further comprise a second snap hook assembly;

said two or more straps further comprise a third strap;

said one or more ring buckles further comprise a third ring buckle;

19

said second strap and said third strap attach to one another with said third ring buckle in the same manner as said first strap and said second strap attach to one another using said first ring buckle; and
 said second snap hook assembly attaches to said third ring buckle.

17. A tank tiedown system for securing a tank during transport in a vehicle, wherein:

said tank tiedown system comprises a perimeter strap assembly, a first hook-and-loop fastener assembly having a first fastener portion and a second fastener portion, a one or more snap hook assemblies, and one or more ring buckles,
 said one or more ring buckles comprise at least a first ring buckle;
 said perimeter strap assembly comprises a first end and a second end;
 said first ring buckle is attached to said second end of said perimeter strap assembly;
 said first fastener portion and said second fastener portion are attached to said first end of said perimeter strap assembly with said first fastener portion more proximate to said first end than said second fastener portion;
 said perimeter strap assembly comprises a strap length;
 said strap length is long enough to secure said tank tiedown system around said tank by
 wrapping said perimeter strap assembly around said tank,
 doubling a portion of said first end back through said first ring buckle, and

20

attaching said first fastener portion to said second fastener portion of said first hook-and-loop fastener assembly;
 said tank tiedown system can comprise a variable diameter, and said tank can comprise a tank diameter;
 said tank tiedown system can be configured to adjust said variable diameter to match said tank diameter and securely tighten around said tank;
 said one or more snap hook assemblies comprise at least a first snap hook assembly;
 said first snap hook assembly attaches to a portion of said perimeter strap assembly and extends outward from said tank with said tank tiedown system attached around said tank;
 said one or more snap hook assemblies are configured to selectively hook and release an anchor point to securely hold said tank with said tank tiedown system within said vehicle;
 said one or more snap hook assemblies further comprise a second snap hook assembly;
 said two or more straps further comprise a third strap;
 said one or more ring buckles further comprise a third ring buckle;
 said second strap and said third strap attach to one another with said third ring buckle in the same manner as said first strap and said second strap attach to one another using said first ring buckle; and
 said second snap hook assembly attaches to said third ring buckle.

* * * * *